



SHANDONG LINGLONG TIRE CO.,LTD.

Add:No.777,Jinlong Road,Zhaoyuan City,Shandong,China

Tel:+86-535-8238901 8242696

Fax:+86-535-8229244

LLIE_sales@linglong.cn

P.c:265406

Http://en.linglong.cn

 **LINGLONG TIRE**

PRODUCT CATALOG



The World At Your Reach

TABLE OF CONTENTS

PCR

SPORT MASTER	05
GREEN-Max	07
COMFORT MASTER	09
GREEN-Max HP010	13
GREEN-Max ECO TOURING	15
GREEN-Max ACRO ^{RFT}	16
GRIP MASTER 4S	17
GREEN-Max All Season	19

SUV

GRIP MASTER C/S	23
GREEN-Max 4x4 HP	25
CROSSWIND H/T	27
CROSSWIND A/T ¹⁰⁰	28
CROSSWIND M/T	29
RADIAL620	30

LT

RADIAL R701	33
GREEN-Max Van	34
GREEN-Max Van HP	35
RADIAL666	36
GREEN-Max Van 4S	37

WIN

GREEN-Max Winter HP	39
GREEN-Max Winter Van	40
GREEN-Max Winter UHP	41
NORD MASTER	43
GREEN-Max Winter Ice I-15	44
GREEN-MAX Winter Ice I-15 SUV	45
GREEN-MAX winter GRIP ²	47
GREEN-MAX winter GRIP	48
GREEN-MAX winter GRIP VAN ²	49
GREEN-MAX winter GRIP SUV	50

PRODUCT CONTENTS



PCR



SPORT MASTER



GREEN-Max



COMFORT MASTER



GREEN-Max HP010



GREEN-Max EcoTouring



GREEN-Max
ACRO^{RFT}



GRIP MASTER 4S



GREEN-Max All Season

THE WORLD AT YOUR REACH



SPORT MASTER

Ultra high performance.

FBU Technology--Update the Wet performance;

VSG Technology--improve the handling performance;

BPT Technology--improve the acture contact area for better the handling performance.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
										RR Level	WG Level	PASS BY NOISE			
										dB	Level				
16	205/45R16 XL	87	Y	7J	545	290	590	206	6.3	D	A	69	A		
	205/50R16 XL	91	Y	6 1/2J	615	290	612	214	6.3	C	A	69	A		
	205/55R16	91	V	6 1/2J	615	250	632	214	7.0	C	A	68	A		
	205/55R16 XL	94	Y	6 1/2J	670	290	632	214	7.0	C	A	69	A		
	215/45R16 XL	90	Y	7J	600	290	600	213	6.3	C	A	69	A		
	225/50R16 XL	96	Y	7J	710	290	632	233	6.3	C	A	69	A		
	*185/55R16 XL	87	Y	6J	545	290	610	194	6.3	D	A	68	A		
	*195/45R16 XL	84	Y	6 1/2J	500	290	582	195	6.3	D	A	69	A		
	*215/40R16 XL	86	Y	7 1/2J	530	290	578	218	6.3	D	A	69	A		
	*215/55R16 XL	97	Y	7J	730	290	642	226	6.3	C	A	69	A		
*225/55R16 XL	99	Y	7J	775	290	654	233	6.3	C	A	69	A			
17	205/45R17 XL	88	Y	7J	560	290	616	206	6.3	D	A	69	A		
	205/50R17 XL	93	Y	6 1/2J	650	290	638	214	6.3	C	A	69	A		
	215/40R17 XL	87	Y	7 1/2J	545	290	604	218	6.3	D	A	69	A		

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
										RR Level	WG Level	PASS BY NOISE			
										dB	Level				
17	215/45R17 XL	91	Y	7J	615	290	626	213	6.3	C	A	69	A		
	215/50R17 XL	95	Y	7J	690	290	648	226	6.3	C	A	69	A		
	215/55R17 XL	98	Y	7J	750	290	668	226	6.3	C	A	69	A		
	225/45R17 XL	94	Y	7 1/2J	670	290	634	225	7.0	C	A	69	A		
	225/50R17 XL	98	Y	7J	750	290	658	233	6.3	C	A	69	A		
	235/45R17 XL	97	Y	8J	730	290	644	236	6.8	C	A	69	A		
	235/50R17 XL	100	Y	7 1/2J	800	290	668	245	6.8	C	A	69	A		
	245/45R17 XL	99	Y	8J	775	290	652	243	6.8	C	A	69	A		
	*195/45R17 XL	85	Y	6 1/2J	515	290	608	195	6.3	D	A	69	A		
	*205/40R17 XL	84	Y	7 1/2J	500	290	596	212	6.3	D	A	69	A		
*225/55R17 XL	101	Y	7J	825	290	680	233	6.3	C	A	69	A			
*245/40R17 XL	95	Y	8 1/2J	690	290	628	248	6.8	C	A	69	A			
18	225/45R18 XL	95	Y	7 1/2J	690	290	659	225	6.3	C	A	69	A		
	245/40R18 XL	97	Y	8 1/2J	730	290	653	248	6.8	C	A	69	A		
	225/40R18 XL	92	Y	8J	630	290	637	230	6.3	C	A	69	A		
	235/40R18 XL	95	Y	8 1/2J	690	290	645	241	6.8	C	A	69	A		
	235/45R18 XL	98	Y	8J	750	290	669	236	7.0	C	A	69	A		
	235/50R18 XL	101	Y	7 1/2J	825	290	693	245	6.8	C	A	69	A		
	245/45R18 XL	100	Y	8J	800	290	677	243	6.8	C	A	69	A		
	255/35R18 XL	94	Y	9J	670	290	635	260	6.8	C	A	70	A		
	*255/45R18 XL	103	Y	8 1/2J	875	290	687	255	6.8	C	A	70	A		
	*265/35R18 XL	97	Y	9 1/2J	730	290	643	271	6.8	C	A	70	A		
19	225/35R19 XL	88	W	8J	560	290	641	230	7.0	D	A	69	A		
	225/35R19 XL	88	Y	8J	560	290	641	230	7.0	D	A	69	A		
	225/40R19 XL	93	Y	8J	650	290	663	230	6.3	C	A	69	A		
	235/40R19 XL	96	Y	8 1/2J	710	290	671	241	6.8	C	A	69	A		
	235/50R19 XL	103	Y	7 1/2J	875	290	719	245	6.8	C	A	69	A		
	245/35R19 XL	93	Y	8 1/2J	650	290	655	248	7.0	D	A	69	A		
	255/35R19 XL	96	Y	9J	710	290	661	260	6.8	C	A	70	A		
	*225/45R19 XL	96	Y	7 1/2J	710	290	685	225	6.3	C	A	69	A		
	*225/55R19 XL	103	Y	7J	875	290	731	233	6.3	C	A	69	A		
	*235/35R19 XL	91	Y	8 1/2J	615	290	647	241	6.8	C	A	69	A		
*245/40R19 XL	98	Y	8 1/2J	750	290	679	248	6.8	C	A	69	A			
*245/45R19 XL	102	Y	8J	850	290	703	243	6.8	C	A	69	A			
*255/30R19 XL	91	Y	9J	615	290	637	260	6.8	D	A	70	A			
*275/40R19 XL	105	Y	9 1/2J	925	290	703	278	6.8	C	A	70	A			
20	215/30R20 XL	82	W	7 1/2J	475	290	638	218	7.0	D	A	69	A		
	245/35R20 XL	95	Y	8 1/2J	690	290	680	248	6.8	C	A	69	A		
	245/40R20 XL	99	Y	8 1/2J	775	290	704	248	6.8	C	A	69	A		
	255/35R20 XL	97	Y	9J	730	290	686	260	6.8	C	A	70	A		
	315/35R20 XL	110	Y	11J	1060	290	728	320	6.8	C	A	72	A		
	*265/30R20 XL	94	Y	9 1/2J	670	290	668	271	6.8	C	A	70	A		
*275/35R20 XL	102	Y	9 1/2J	850	290	700	278	6.8	C	A	70	A			
21	*245/35R21 XL	96	Y	8 1/2J	710	290	705	248	6.8	C	A	69	A		
	*295/35R21 XL	107	Y	10 1/2J	975	290	739	301	6.8	C	A	72	A		
22	255/35R22 XL	99	Y	9J	775	290	737	260	6.8	C	A	70	A		
	285/35R22 XL	106	Y	10J	950	290	759	290	6.8	C	A	72	A		
	*265/30R22 XL	97	Y	9 1/2J	730	290	719	271	6.8	C	A	70	A		

Notes: * under development

GREEN-Max

UHP Tire with Excellent Wet Grip and Low Noise.

Excellent handling performance;

Improved drainage performance to effectively reduce risk of hydroplaning;

Superior driving stability;

Comfortable ride;

Designed to fit premium cars and sports cars.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
												dB	Level
15	185/45R15	75	V	6J	387	250	547	183	7.5	D	B	70	B
16	195/45R16 XL	84	V	6 1/2J	500	290	582	195	7.6	D	B	72	B
	205/45R16 XL	87	W	7J	545	290	590	206	7.6	D	B	72	B
	205/50R16	87	W	6 1/2J	545	250	612	214	7.6	C	B	71	B
	205/50R16	87	V	6 1/2J	545	250	612	214	7.6	C	B	71	B
	205/55R16 XL	94	W	6 1/2J	670	290	632	214	7.6	C	B	72	B
	215/40R16 XL	86	W	7 1/2J	530	290	578	218	7.6	D	B	72	B
	215/45R16 XL	90	V	7J	600	290	600	213	7.3	C	B	72	B
	215/55R16 XL	97	W	7J	730	290	642	226	7.6	C	B	72	B
	225/50R16 XL	96	V	7J	710	290	632	233	7.6	C	B	72	B
	225/55R16	95	V	7J	690	250	654	233	7.5	D	B	71	B
17	185/35R17 XL	82	V	6 1/2J	475	290	562	188	7.5	D	B	72	B
	195/40R17 XL	81	V	8J	462	290	588	200	7.5	C	B	72	B
	205/40R17 XL	84	W	7 1/2J	500	290	596	212	7.6	D	B	72	B
	205/45R17 XL	88	W	7J	560	290	616	206	7.6	D	B	72	B
	205/45R17 XL	88	V	7J	560	290	616	206	7.6	D	B	72	B

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
												dB	Level
17	205/50R17 XL	93	W	6 1/2J	650	290	638	214	7.6	D	B	72	B
	215/40R17 XL	87	W	7 1/2J	545	290	604	218	7.6	D	B	72	B
	215/45R17 XL	91	W	7J	615	290	626	213	7.6	D	B	72	B
	215/50R17 XL	95	V	7J	690	290	648	226	7.5	D	B	72	B
	215/50R17 XL	95	W	7J	690	290	648	226	7.5	D	B	72	B
	215/55R17	94	V	7J	670	250	668	226	7.5	D	B	71	B
	215/55R17 XL	98	W	7J	750	290	668	226	7.5	D	B	72	B
	225/45R17 XL	94	W	7 1/2J	670	290	634	225	7.6	D	B	72	B
	225/50R17 XL	98	W	7J	750	290	658	233	7.6	C	B	72	B
	225/55R17	97	W	7J	730	250	680	233	7.6	D	B	71	B
	225/55R17 XL	101	W	7J	825	290	680	233	7.6	D	B	72	B
	235/45ZR17 XL	97	W	8J	730	290	644	236	7.6	D	B	72	B
	235/50R17	96	Y	7 1/2J	710	250	668	245	7.5	D	B	71	B
	245/40R17	91	W	8 1/2J	615	250	628	248	7.5	D	B	71	B
245/45R17 XL	99	W	8J	775	290	652	243	7.6	C	B	72	B	
18	215/35R18 XL	84	W	7 1/2J	500	290	607	218	7.6	D	B	72	B
	215/40R18 XL	89	W	7 1/2J	580	290	629	218	7.5	D	B	72	B
	215/45R18 XL	93	W	7J	650	290	651	213	7.5	D	B	72	B
	225/40R18 XL	92	W	8J	630	290	637	230	7.6	D	B	72	B
	225/45R18 XL	95	W	7 1/2J	690	290	659	225	7.6	D	B	72	B
	235/40R18 XL	95	W	8 1/2J	690	290	645	241	7.6	D	B	72	B
	235/45R18 XL	98	Y	8J	750	290	669	236	7.3	C	B	72	B
	235/50R18 XL	101	W	7 1/2J	825	290	693	245	7.6	C	B	72	B
	245/40R18 XL	97	W	8 1/2J	730	290	653	248	7.6	D	B	72	B
	245/45R18 XL	100	W	8J	800	290	677	243	7.6	C	B	72	B
	255/35R18 XL	94	Y	9J	670	290	635	260	7.5	D	B	73	B
	255/45R18 XL	103	W	8 1/2J	875	290	687	255	7.6	C	B	73	B
	265/35R18 XL	97	Y	9 1/2J	730	290	643	271	7.5	D	B	73	B
	19	225/35R19 XL	88	W	8J	560	290	641	230	7.6	D	B	72
225/45R19 XL		96	W	7 1/2J	710	290	685	225	7.6	D	B	72	B
235/35R19 XL		91	W	8 1/2J	615	290	647	241	7.6	D	B	72	B
235/55R19 XL		105	W	7 1/2J	925	290	741	245	7.5	B	B	72	B
245/35R19 XL		93	Y	8 1/2J	650	290	655	248	7.5	D	B	72	B
245/40R19 XL		98	W	8 1/2J	750	290	679	248	7.5	D	B	72	B
245/45R19		98	Y	8J	750	250	703	243	7.5	D	B	71	B
265/30R19 XL		93	W	9 1/2J	650	290	643	271	7.6	D	B	73	B
20	215/30R20 XL	82	W	7 1/2J	475	290	638	218	7.5	D	B	72	B
	225/30R20 XL	85	W	8J	515	290	644	230	7.5	C	B	72	B
	225/35R20 XL	90	Y	8J	600	290	666	230	7.5	D	B	72	B
	235/30R20 XL	88	Y	8 1/2J	560	290	650	242	7.5	D	B	72	B
	245/35R20 XL	95	Y	8 1/2J	690	290	680	248	7.5	D	B	72	B



COMFORT MASTER

NEW
PCR TYRE



HP Tire with Good Handling Performance and Low Noise.

Comfortable and quiet ride;

Low rolling resistance for better fuel efficiency;

Enhanced wet grip to effectively reduce risk of hydroplaning.

THREE GROOVES

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE dB	Level
13	145/70R13	71	T	4.50B	345	250	534	150	5.7	D	B	70	B
	155/70R13	75	T	4.50B	387	250	548	157	6.2	D	B	70	B
	155/80R13	79	T	4.50B	437	250	578	157	6.2	D	B	70	B
	175/70R13	82	T	5.00B	475	250	576	177	6.2	D	B	70	B
14	155/65R14	75	H	4 1/2J	387	250	558	157	6.2	C	B	70	B
	155/65R14	75	T	4 1/2J	387	250	558	157	6.2	D	B	70	B
	165/60R14	75	H	5J	387	250	554	170	6.2	C	B	70	B
	165/65R14	79	H	5J	437	250	570	170	6.2	D	B	70	B
	165/65R14	79	T	5J	437	250	570	170	6.2	C	B	70	B
	165/70R14	81	T	5J	462	250	588	170	6.2	C	B	70	B
	165/70R14 XL	85	T	5J	515	290	588	170	6.2	C	B	71	B
	175/60R14	79	H	5J	437	250	566	177	6.2	C	B	70	B
	175/65R14	82	T	5J	475	250	584	177	6.2	C	B	70	B
	175/65R14	82	H	5J	475	250	584	177	6.2	C	B	70	B
	175/65R14 XL	86	T	5J	530	290	584	177	6.2	C	B	71	B
	175/70R14	84	T	5J	500	250	602	177	6.2	D	B	70	B
175/70R14 XL	88	T	5J	560	290	602	177	6.2	C	B	71	B	
15	145/65R15	72	T	4 1/2J	355	250	569	150	6.2	C	B	67	A
	155/60R15	74	T	4 1/2J	375	250	567	157	6.2	C	B	70	B
	165/55R15	75	V	5J	387	250	563	170	6.2	D	B	70	B
	165/60R15	77	H	5J	412	250	579	170	6.2	C	B	70	B
	165/60R15	77	T	5J	412	250	579	170	6.2	D	B	70	B
	165/65R15	81	H	5J	462	250	595	170	6.2	D	B	70	B
	165/65R15	81	T	5J	462	250	595	170	6.2	D	B	70	B
	175/55R15	77	T	5 1/2J	412	250	573	182	6.2	D	B	70	B
	175/60R15	81	H	5J	462	250	591	177	6.2	C	B	70	B
	175/60R15	81	V	5J	462	250	591	177	6.2	C	B	70	B
	175/65R15	84	H	5J	500	250	609	177	6.2	D	B	70	B
	175/65R15	84	T	5J	500	250	609	177	6.2	D	B	70	B
	16	175/60R16	82	H	5J	475	250	616	177	6.2	C	B	70

FOUR GROOVES

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details				
										RR Level	WG Level	PASS BY NOISE		
												dB	Level	
14	185/55R14	80	H	6J	450	250	560	194	6.7	D	B	70	B	
	185/60R14	82	H	5 1/2J	475	250	578	189	6.7	D	B	70	B	
	185/60R14	82	T	5 1/2J	475	250	578	189	6.7	D	B	70	B	
	185/65R14	86	H	5 1/2J	530	250	596	189	6.7	C	B	70	B	
	185/65R14	86	T	5 1/2J	530	250	596	189	6.7	D	B	70	B	
	185/70R14	88	T	5 1/2J	560	250	616	189	6.7	C	B	70	B	
	195/60R14	86	H	6J	530	250	590	201	6.7	C	B	71	B	
	205/70R14	94	T	6J	670	250	644	209	6.7	C	B	71	B	
	195/65R14	89	H	6J	580	250	610	201	6.7	C	B	71	B	
	195/70R14	91	T	6J	615	250	630	201	6.7	C	B	71	B	
	15	185/55R15	82	V	6J	475	250	585	194	6.7	D	B	70	B
		185/60R15	84	H	5 1/2J	500	250	603	189	6.7	D	B	70	B
185/60R15		84	T	5 1/2J	500	250	603	189	6.7	D	B	70	B	
185/60R15 XL		88	H	5 1/2J	560	290	603	189	6.7	C	B	71	B	
185/65R15		88	H	5 1/2J	560	250	621	189	6.7	C	B	70	B	
185/65R15		88	T	5 1/2J	560	250	621	189	6.7	C	B	70	B	
195/50R15		82	V	6J	475	250	577	201	6.7	D	B	71	B	
195/55R15		85	H	6J	515	250	595	201	6.7	D	B	71	B	
195/55R15		85	V	6J	515	250	595	201	6.7	D	B	71	B	
195/60R15		88	H	6J	560	250	615	201	6.7	C	B	71	B	
195/60R15		88	V	6J	560	250	615	201	6.7	C	B	71	B	
195/65R15		91	H	6J	615	250	635	201	6.7	C	B	71	B	
195/65R15		91	T	6J	615	250	635	201	6.7	C	B	71	B	
195/65R15		91	V	6J	615	250	635	201	6.7	C	B	71	B	
195/65R15 XL		95	H	6J	690	290	635	201	6.7	C	B	72	B	
205/60R15		91	H	6J	615	250	627	209	6.7	C	B	71	B	
205/60R15		91	V	6J	615	250	627	209	6.7	C	B	71	B	
205/70R15		96	T	6J	710	250	669	209	6.7	C	B	71	B	
215/60R15		94	H	6 1/2J	670	250	639	221	6.7	C	B	71	B	
17		185/55R15	82	H	6J	475	250	585	194	6.7	D	B	70	B
	185/65R15 XL	92	T	5 1/2J	630	290	621	189	6.7	C	B	71	B	
	195/65R15 XL	95	T	6J	690	290	635	201	6.7	C	B	72	B	
	205/50R15	86	V	6 1/2J	530	250	587	214	6.7	D	B	71	B	
	205/55R15	88	V	6 1/2J	560	250	607	214	6.7	C	B	71	B	
	205/65R15	94	H	6J	670	250	647	209	6.7	C	B	71	B	
	205/65R15	94	V	6J	670	250	647	209	6.7	C	B	71	B	
	215/65R15 XL	100	H	6 1/2J	800	290	661	221	6.7	C	B	72	B	
	215/65R15	96	H	6 1/2J	710	250	661	221	6.7	C	B	71	B	
	16	185/50R16	81	V	6J	462	250	592	202	6.7	D	B	70	B
		185/55R16	83	V	6J	487	250	610	194	6.7	D	B	70	B
		195/50R16	84	V	6J	500	250	602	201	6.7	D	B	71	B
		195/50R16 XL	88	V	6J	560	290	602	201	6.7	C	B	72	B
		195/55R16	87	H	6J	545	250	620	201	6.7	C	B	71	B
195/55R16		87	V	6J	545	250	620	201	6.7	C	B	71	B	
195/55R16 XL		91	V	6J	615	290	620	201	6.7	C	B	72	B	
205/50R16		87	H	6 1/2J	545	250	612	214	6.7	D	B	71	B	
205/50R16		87	V	6 1/2J	545	250	612	214	6.7	D	B	71	B	
205/55R16		91	H	6 1/2J	615	250	632	214	6.5	C	B	71	B	
205/55R16		91	V	6 1/2J	615	250	632	214	6.5	C	B	71	B	
205/60R16		92	H	6J	630	250	652	209	6.8	C	B	71	B	
205/60R16	92	V	6J	630	250	652	209	6.7	C	B	71	B		
205/60R16 XL	96	V	6J	710	290	652	209	6.7	C	B	72	B		
205/65R16	95	H	6J	690	250	672	209	6.7	C	B	71	B		
215/55R16	93	V	7J	650	250	642	226	6.7	C	B	71	B		
215/65R16	98	H	6 1/2J	750	250	686	221	6.7	C	B	71	B		
225/50R16	92	V	7J	630	250	632	233	7	C	B	71	B		
225/60R16	98	V	6 1/2J	750	250	676	228	7	C	B	71	B		
225/70R16	103	H	6 1/2J	875	250	722	228	7	C	B	71	B		
195/60R16	89	H	6J	580	250	640	201	6.7	C	B	71	B		
195/60R16	89	V	6J	580	250	640	201	6.7	C	B	71	B		
215/60R16	95	H	6 1/2J	690	250	664	221	6.7	C	B	71	B		
215/60R16	95	V	6 1/2J	690	250	664	221	6.7	C	B	71	B		
215/60R16 XL	99	H	6 1/2J	775	290	664	221	6.7	C	B	72	B		
215/60R16 XL	99	V	6 1/2J	775	290	664	221	6.7	C	B	72	B		
225/55R16 XL	99	H	7J	775	290	654	233	7	B	B	72	B		
225/55R16 XL	99	V	7J	775	290	654	233	7	B	B	72	B		
235/60R16	100	H	7J	800	250	688	240	7.5	C	B	71	B		
255/70R16 XL	115	H	7 1/2J	1215	290	764	260	8	C	B	73	B		
205/50R17 XL	93	V	6 1/2J	650	290	638	214	6.7	C	B	72	B		
215/50R17 XL	95	V	7J	690	290	648	226	6.7	C	B	72	B		
215/55R17	94	V	7J	670	250	668	226	6.7	C	B	71	B		
215/60R17	96	H	6 1/2J	710	250	690	221	6.7	C	B	71	B		
225/50R17	94	V	7J	670	250	658	233	7	C	B	71	B		
225/50R17 XL	98	V	7J	750	290	658	233	7	C	B	72	B		
225/60R17	99	H	6 1/2J	775	250	702	228	7	C	B	71	B		
225/60R17	99	V	6 1/2J	775	250	702	228	7	C	B	71	B		
225/65R17	102	H	6 1/2J	850	250	724	228	7	C	B	71	B		
235/55R17	99	V	7 1/2J	775	250	690	245	7.5	C	B	71	B		
205/55R17 XL	95	V	6 1/2J	690	290	658	214	6.7	C	B	72	B		
235/60R17	102	H	7J	850	250	714	240	7.5	C	B	71	B		

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details				
										RR Level	WG Level	PASS BY NOISE		
												dB	Level	
14	185/55R14	80	H	6J	450	250	560	194	6.7	D	B	70	B	
	185/60R14	82	H	5 1/2J	475	250	578	189	6.7	D	B	70	B	
	185/60R14	82	T	5 1/2J	475	250	578	189	6.7	D	B	70	B	
	185/65R14	86	H	5 1/2J	530	250	596	189	6.7	C	B	70	B	
	185/65R14	86	T	5 1/2J	530	250	596	189	6.7	D	B	70	B	
	185/70R14	88	T	5 1/2J	560	250	616	189	6.7	C	B	70	B	
	195/60R14	86	H	6J	530	250	590	201	6.7	C	B	71	B	
	205/70R14	94	T	6J	670	250	644	209	6.7	C	B	71	B	
	195/65R14	89	H	6J	580	250	610	201	6.7	C	B	71	B	
	195/70R14	91	T	6J	615	250	630	201	6.7	C	B	71	B	
	15	185/55R15	82	V	6J	475	250	585	194	6.7	D	B	70	B
		185/60R15	84	H	5 1/2J	500	250	603	189	6.7	D	B	70	B
185/60R15		84	T	5 1/2J	500	250	603	189	6.7	D	B	70	B	
185/60R15 XL		88	H	5 1/2J	560	290	603	189	6.7	C	B	71	B	
185/65R15		88	H	5 1/2J	560	250	621	189	6.7	C	B	70	B	
185/65R15		88	T	5 1/2J	560	250	621	189	6.7	C	B	70	B	
195/50R15		82	V	6J	475	250	577	201	6.7	D	B	71	B	
195/55R15		85	H	6J	515	250	595	201	6.7	D	B	71	B	
195/55R15		85	V	6J	515	250	595	201	6.7	D	B	71	B	
195/60R15		88	H	6J	560	250	615	201	6.7	C	B	71	B	
195/60R15		88	V	6J	560	250	615	201	6.7	C	B	71	B	
195/65R15		91	H	6J	615	250	635	201	6.7	C	B	71	B	
195/65R15		91	T	6J	615	250	635	201	6.7	C	B	71	B	
195/65R15		91	V	6J	615	250	635	201	6.7	C	B	71	B	
195/65R15 XL		95	H	6J	690	290	635	201	6.7	C	B	72	B	
205/60R15		91	H	6J	615	250	627	209	6.7	C	B	71	B	
205/60R15		91	V	6J	615	250	627	209	6.7	C	B	71	B	
205/70R15		96	T	6J	710	250	669	209	6.7	C	B	71	B	
215/60R15		94	H	6 1/2J	670	250	639	221	6.7	C	B	71	B	
17		185/55R15	82	H	6J	475	250	585	194	6.7	D	B	70	B
	185/65R15 XL	92	T	5 1/2J	630	290	621	189	6.7	C	B	71	B	
	195/65R15 XL	95	T	6J	690	290	635	201	6.7	C	B	72	B	
	205/50R15	86	V	6 1/2J	530	250	587	214	6.7	D	B	71	B	
	205/55R15	88	V	6 1/2J	560	250	607	214	6.7	C	B	71	B	
	205/65R15	94	H	6J	670	250	647	209	6.7	C	B	71	B	
	20													

GREEN-Max HP010



HP Tire with Good Handling Performance and Low Noise.

Comfortable and quiet ride;

Low rolling resistance for better fuel efficiency;

Enhanced wet grip to effectively reduce risk of hydroplaning.

THREE GROOVES

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
14	165/60R14	75	H	5J	387	250	554	170	7.3	D	B	70	B
	175/65R14	82	H	5J	475	250	584	177	7.3	C	B	70	B
15	165/50R15	73	V	5J	365	250	547	170	7.4	D	B	70	B
	165/55R15	75	V	5J	387	250	563	170	7.3	D	B	70	B
	165/60R15	77	H	5J	412	250	579	170	7.3	C	B	70	B
	175/60R15	81	H	5J	462	250	591	177	7.3	C	B	70	B
	175/65R15	84	H	5J	500	250	609	177	7.3	C	B	70	B
16	165/45R16 XL	74	V	5 1/2J	375	290	554	165	7.4	D	B	71	B
17	165/40R17 XL	75	V	6J	387	290	564	170	7.4	D	B	71	B

FOUR GROOVES

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
14	185/55R14	80	H	6J	450	250	560	194	7.7	D	B	70	B
	185/60R14	82	H	5 1/2J	475	250	578	189	7.7	D	B	70	B
	185/65R14	86	H	5 1/2J	530	250	596	189	7.8	C	B	70	B
	195/65R14	89	H	6J	580	250	610	201	7.2	C	B	71	B
15	185/55R15	82	V	6J	475	250	585	194	7.7	C	B	70	B
	185/60R15 XL	88	H	5 1/2J	560	290	603	189	7.7	C	B	71	B
	185/65R15	88	H	5 1/2J	560	250	621	189	7.7	C	B	70	B
	195/50R15	82	V	6J	475	250	577	201	7.8	C	B	71	B
	195/55R15	85	V	6J	515	250	595	201	7.8	C	B	71	B
	195/60R15	88	H/V	6J	560	250	615	201	6.0	C	B	71	B
	195/65R15	91	H/V	6J	615	250	635	201	7.8	C	B	71	B
	205/55R15	88	V	6 1/2J	560	250	607	214	7.2	C	B	71	B
	205/60R15	91	H/V	6J	615	250	627	209	7.8	C	B	71	B
	205/65R15	94	H/V	6J	670	250	647	209	7.8	C	B	71	B
	215/65R15 XL	100	H	6 1/2J	800	290	661	221	7.8	C	B	72	B
	16	185/50R16	81	H	6J	462	250	592	194	7.5	C	B	71
195/50R16 XL		88	V	6J	560	290	602	201	7.5	C	B	71	B
195/55R16		87	V	6J	545	250	620	201	7.5	C	B	71	B
195/55R16 XL		91	H	6J	615	290	620	201	7.7	C	B	71	B
195/60R16		89	H	6J	580	250	640	201	7.5	C	B	71	B
205/50R16		87	V	6 1/2J	545	250	612	214	7.8	C	B	71	B
205/55R16		91	H/V	6 1/2J	615	250	632	214	7.8	C	B	71	B
205/60R16		92	H/V	6J	630	250	652	209	7.8	C	B	71	B
205/65R16		95	H	6J	690	250	672	209	7.8	C	B	71	B
215/60R16		95	H	6 1/2J	690	250	664	221	7.8	C	B	71	B
215/60R16 XL		99	H/V	6 1/2J	775	290	664	221	7.7	C	B	71	B
215/65R16		98	H	6 1/2J	750	250	686	221	7.7	C	B	71	B
225/65R16		100	H	6 1/2J	800	250	698	228	8.6	C	B	71	B
225/70R16		103	H	6 1/2J	875	250	722	228	8.6	C	B	71	B
17	235/65R16	103	H	7J	875	250	712	240	8.2	C	B	71	B
	255/65R16	109	H	7 1/2J	1030	250	738	260	8.1	C	B	71	B
	205/55R17 XL	95	V	6 1/2J	690	290	658	214	7.5	C	B	71	B
	215/60R17	96	H	6 1/2J	710	250	690	221	7.8	C	B	71	B
	225/65R17	102	H	6 1/2J	850	250	724	228	8.6	C	B	71	B

GREEN-Max EcoTouring

Eco-friendly Tire.

Low resistance;

Low noise;

Excellent wet performance.



GREEN-Max ACRO^{RFT}

Super ability Run-Flat tire.

Asymmetric tread pattern design provides more stable driving and riding;

Big shoulder blocks to effectively improve handling performance;

Carry linglong LRS run-flat technology, for the safety of the vehicle driving escort.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
										RR Level	WG Level	PASS BY NOISE			
											dB	Level			
16	225/55RF16	95	W	7J	690	250	654	233	7.0	D	B	71	B		
17	225/45RF17	91	W	7 1/2J	615	250	634	225	7.0	D	B	71	B		
	225/50RF17	94	W	7J	670	250	658	233	7.5	D	B	71	B		
18	225/55RF17	97	W	7J	730	250	680	233	7.0	D	B	71	B		
	245/40RF18	93	W	8 1/2J	650	250	653	248	7.0	D	B	71	B		
	245/45RF18	96	W	8J	710	250	677	243	7.0	D	B	71	B		
	245/50RF18	100	W	7 1/2J	800	250	703	253	7.0	D	B	71	B		
	255/55RF18	105	W	8J	925	250	737	265	7.0	D	B	72	B		
19	* 225/45RF18	91	W	7 1/2J	615	250	659	225	7.0	/	/	/	/		
	225/40RF19	89	W	8J	580	250	663	230	7.0	D	B	71	B		
	245/40RF19	94	W	8 1/2J	670	250	679	248	7.0	D	B	71	B		
	245/45RF19	98	W	8J	750	250	703	243	7.0	D	B	71	B		
	255/50RF19	103	W	8J	875	250	739	265	7.0	D	B	72	B		
	255/55RF19	107	W	8J	975	250	763	265	7.0	D	B	72	B		
	* 255/35RF19	92	Y	9J	630	250	661	260	7.0	/	/	/	/		
	* 275/35RF19	96	Y	9 1/2J	710	250	675	278	7.0	/	/	/	/		
20	* 275/40RF19	101	Y	9 1/2J	825	250	703	278	7.0	/	/	/	/		
	275/40RF20	102	W	9 1/2J	850	250	728	278	7.0	C	A	72	B		
	275/45RF20	106	W	9J	950	250	756	273	7.0	D	A	72	B		
	* 245/40RF20 XL	99	Y	8 1/2J	775	290	704	248	7.0	/	/	/	/		
	* 275/35RF20 XL	102	Y	9 1/2J	850	290	700	278	7.0	/	/	/	/		
	* 305/40RF20 XL	112	Y	11J	1120	290	752	313	7.0	/	/	/	/		
	* 315/35RF20 XL	110	Y	11J	1060	290	728	320	7.0	/	/	/	/		

Notes: * under development

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
										RR Level	WG Level	PASS BY NOISE			
											dB	Level			
12	145/70R12	69	S	4.50B	325	250	509	150	6.2	C	C	70	B		
13	145/70R13	71	T	4.50B	345	250	534	150	7.3	D	C	70	B		
	145/80R13	75	T	4.00B	387	240	562	145	7.1	D	C	70	B		
	155/65R13	73	T	4.50B	365	250	532	157	7.3	D	C	70	B		
	155/70R13	75	T	4.50B	387	250	548	157	7.3	D	C	70	B		
	155/80R13	79	T	4.50B	437	240	578	157	7.3	D	C	70	B		
	165/65R13	77	T	5.00B	412	250	544	170	6.0	D	C	70	B		
	165/70R13	79	T	5.00B	437	250	562	170	6.0	C	C	70	B		
	175/60R13	77	H	5.00B	412	250	540	177	7.3	D	C	70	B		
	175/65R13	80	T	5.00B	450	250	558	177	7.3	D	C	70	B		
	175/70R13	82	T	5.00B	475	250	576	177	6.0	D	C	70	B		
14	155/65R14	75	T	4 1/2J	387	250	558	157	7.3	D	C	70	B		
	165/65R14	79	T	5J	437	250	570	170	7.3	D	C	70	B		
	165/70R14	81	T	5J	462	250	588	170	7.3	D	C	70	B		
	175/65R14	82	T	5J	475	250	584	177	6.0	C	C	70	B		
	175/65R14 XL	86	T	5J	530	290	584	177	6.0	C	C	71	B		
	175/70R14	84	T	5J	500	250	602	177	7.3	D	C	70	B		
	175/70R14 XL	88	T	5J	560	290	602	177	7.3	D	C	71	B		
	185/65R14	86	T	5 1/2J	530	250	596	189	7.5	C	C	70	B		
	185/70R14	88	T	5 1/2J	560	250	616	189	7.7	C	C	70	B		
	195/70R14	91	T	6J	615	250	630	201	7.3	C	C	71	B		
15	185/65R15	88	T	5 1/2J	560	250	621	189	7.7	C	C	70	B		
	185/65R15 XL	92	T	5 1/2J	630	290	621	189	7.7	C	C	70	B		
	195/65R15	91	T	6J	615	250	635	201	6.0	C	C	70	B		
	195/65R15 XL	95	T	6J	690	290	635	201	6.0	C	C	71	B		
	235/75R15	105	T	6 1/2J	925	250	733	235	7.9	D	C	71	B		

GRIP MASTER 4S

Excellent dry wetland braking performance
Wet grip B level

Single direction pattern of the four seasons;

Groove pattern block Yang break air flow, reduce the production pattern noise;

High density pattern sheet steel, ascend snow tyres grip and wetlands;

Using 3 d steel sheets, balanced pattern piece of rigid, promote tire braking performance.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
13	155/80R13	79	T	4.50B	437	240	578	157	7.0
	* 155/70R13	75	T	4.50B	387	250	548	157	/
	* 165/70R13	79	T	5.00B	437	250	562	170	/
14	155/65R14	75	T	4 1/2J	387	250	558	157	7.0
	165/70R14	81	T	5J	462	250	588	170	7.0
	175/65R14	82	T	5J	475	250	584	177	7.0
	185/60R14	82	H	5 1/2J	475	250	578	189	7.0
	* 165/60R14	75	H	5J	387	250	554	170	/
	* 165/65R14	79	T	5J	437	250	570	170	/
	* 175/70R14 XL	88	T	5J	560	290	602	177	/
15	* 185/65R14	86	H	5 1/2J	530	250	596	189	/
	185/55R15	82	H	6J	475	250	585	194	7.0
	185/60R15 XL	88	H	5 1/2J	560	290	603	189	7.0
	185/65R15	88	H	5 1/2J	560	250	621	189	7.0
	195/50R15 XL	86	H	6J	530	290	577	201	7.0
	195/55R15	85	H	6J	515	250	595	201	7.0
	195/60R15	88	H	6J	560	250	615	201	7.0
	195/65R15	91	H	6J	615	250	635	201	7.0
	* 165/65R15	81	T	5J	462	250	595	170	/
	* 175/65R15 XL	88	T	5J	560	290	609	177	/
* 205/65R15	94	H	6J	670	250	647	209	/	

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
16	195/45R16 XL	84	V	6 1/2J	500	290	582	195	7.0
	195/55R16	87	V	6J	545	250	620	201	7.0
	205/55R16	91	V	6 1/2J	615	250	632	214	7.0
	205/60R16 XL	96	V	6J	710	290	652	209	7.0
	215/55R16 XL	97	V	7J	730	290	642	226	7.0
	215/60R16 XL	99	V	6 1/2J	775	290	664	221	7.0
	245/70R16	107	H	7J	975	250	750	248	7.0
	* 215/65R16 XL	102	V	6 1/2J	850	290	638	221	/
	* 215/70R16	100	H	6 1/2J	800	250	686	221	/
	17	205/50R17 XL	93	V	6 1/2J	650	290	708	214
205/55R17 XL		95	W	6 1/2J	690	290	658	214	7.0
215/60R17 XL		100	V	6 1/2J	800	290	690	221	7.0
225/45R17 XL		94	W	7 1/2J	670	290	634	225	7.0
225/50R17 XL		98	V	7J	750	290	658	233	7.5
* 205/45R17 XL		88	W	7J	560	290	616	206	/
* 215/40R17 XL		87	V	7 1/2J	545	290	604	218	/
* 215/45R17 XL		91	W	7J	615	290	626	213	/
* 215/50R17 XL		95	W	7J	690	290	648	226	/
* 215/55R17 XL		98	V	7J	750	290	668	226	/
* 225/55R17 XL		101	V	7J	825	290	680	233	/
* 225/60R17 XL		103	V	6 1/2J	875	290	702	228	/
* 225/65R17 XL		106	V	6 1/2J	950	290	724	228	/
* 235/45R17 XL		97	W	8J	730	290	644	236	/
* 235/55R17 XL		103	W	7 1/2J	875	290	690	245	/
* 235/65R17 XL	108	V	7J	1000	290	738	240	/	
* 245/45R17 XL	99	W	8J	775	290	652	243	/	
18	215/40R18 XL	89	W	7 1/2J	580	290	629	218	7.0
	215/50R18 XL	96	W	7J	710	290	673	226	7.0
	235/45R18 XL	98	W	8J	750	290	669	236	7.0
	235/55R18	100	W	7 1/2J	800	250	715	245	7.0
	245/40R18 XL	97	W	8 1/2J	730	290	653	248	7.0
	* 215/55R18 XL	99	W	7J	775	290	693	226	/
19	* 225/40R18 XL	92	W	8J	630	290	637	230	/
	* 225/45R18 XL	95	W	7 1/2J	690	290	659	225	/
	225/45R19 XL	96	W	7 1/2J	710	290	685	225	7.0
	245/45R19 XL	102	W	8J	850	290	703	243	7.0
	* 225/35R19 XL	88	W	8J	560	290	641	230	/
* 235/35R19 XL	91	W	8 1/2J	615	290	647	241	/	

Notes: *under development

GREEN-Max All Season

All Season Tire.

Excellent handling;

Lower rolling resistance;

All season tire which is applicable to different weather and road conditions.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
13	145/70R13	71	T	4.50B	345	250	534	150	6.2	D	C	71	B
	145/80R13	75	T	4.00B	387	240	562	145	6.2	D	C	71	B
	155/65R13	73	T	4.50B	365	250	532	157	6.2	D	C	71	B
	155/70R13	75	T	4.50B	387	250	548	157	7.0	D	C	71	B
	155/80R13	79	T	4.50B	437	240	578	157	7.0	D	C	71	B
	165/70R13	79	T	5.00B	437	250	562	170	7.0	D	C	71	B
	175/65R13	80	T	5.00B	450	250	558	177	6.2	C	C	71	B
	175/70R13	82	T	5.00B	475	250	576	177	7.0	C	C	71	B
14	155/65R14	75	T	4 1/2J	387	250	558	157	7.0	D	C	71	B
	165/60R14	75	H	5J	387	250	554	170	7.0	D	C	71	B
	165/65R14	79	T	5J	437	250	570	170	7.0	D	C	71	B
	165/70R14	81	T	5J	462	250	588	170	7.0	C	C	71	B
	175/65R14	82	T	5J	475	250	584	177	7.0	C	C	71	B
	175/70R14 XL	88	T	5J	560	290	602	177	7.0	C	C	71	B
	175/80R14	88	T	5J	560	240	636	177	6.2	C	C	71	B
	185/55R14	80	H	6J	450	250	560	194	6.2	C	C	71	B
	185/60R14	82	H	5 1/2J	475	250	578	189	7.0	C	C	71	B
	185/65R14	86	H	5 1/2J	530	250	596	189	6.2	C	C	71	B
15	185/70R14	88	H	5 1/2J	560	250	616	189	6.2	C	C	71	B
	195/70R14	91	T	6J	615	250	630	201	6.7	C	C	72	B
	165/60R15	77	H	5J	412	250	579	170	7.0	C	C	71	B
	165/65R15	81	T	5J	462	250	595	170	6.2	D	C	71	B
	175/65R15 XL	88	T	5J	560	290	609	177	7.0	C	C	71	B
	185/55R15	82	H	6J	475	250	585	194	7.0	C	C	71	B
	185/60R15 XL	88	H	5 1/2J	560	290	603	189	7.0	C	C	71	B
	185/65R15	88	H	5 1/2J	560	250	621	189	7.0	C	C	71	B

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
15	195/50R15 XL	86	H	6J	530	290	577	201	7.0	C	C	72	B
	195/55R15	85	H	6J	515	250	595	201	7.0	C	C	72	B
	195/60R15	88	H	6J	560	250	615	201	7.0	C	C	72	B
	195/65R15	91	H	6J	615	250	635	201	7.0	C	C	72	B
	205/65R15	94	H	6J	670	250	647	209	7.0	B	D	72	B
16	215/65R15	96	H	6 1/2J	710	250	661	221	6.7	C	D	72	B
	195/45R16 XL	84	H	6 1/2J	500	290	582	195	6.7	C	C	72	B
	195/50R16 XL	88	V	6J	560	290	602	201	6.7	C	C	72	B
	195/55R16	87	H	6J	545	250	620	201	7.0	C	C	72	B
	205/45R16 XL	87	V	7J	545	290	590	206	6.7	C	C	72	B
	205/55R16	91	V	6 1/2J	615	250	632	214	7.0	C	C	72	B
	205/60R16 XL	96	H	6J	710	290	652	209	7.0	B	D	72	B
	215/45R16 XL	90	V	7J	600	290	600	213	6.7	C	D	72	B
	215/55R16 XL	97	V	7J	730	290	642	226	7.0	B	D	72	B
	215/60R16 XL	99	H	6 1/2J	775	290	664	221	7.0	B	D	72	B
	215/65R16 XL	102	V	6 1/2J	850	290	686	221	6.7	C	D	72	B
	215/70R16	100	H	6 1/2J	800	250	708	221	6.7	C	D	72	B
	225/55R16 XL	99	V	7J	775	290	654	233	6.7	B	D	72	B
	225/60R16 XL	102	V	6 1/2J	850	290	676	228	6.7	C	D	72	B
	17	205/45R17 XL	88	V	7J	560	290	616	206	6.7	C	C	72
205/50R17 XL		93	V	6 1/2J	650	290	638	214	7.0	B	C	72	B
205/55R17 XL		95	V	6 1/2J	690	290	658	214	7.0	B	C	72	B
215/40R17 XL		87	V	7 1/2J	545	290	604	218	6.7	C	D	72	B
215/45R17 XL		91	V	7J	615	290	626	213	6.7	C	D	72	B
215/50R17 XL		95	V	7J	690	290	648	226	7.0	B	D	72	B
215/55R17 XL		98	V	7J	750	290	668	226	7.0	B	D	72	B
215/60R17 XL		100	V	6 1/2J	800	290	690	221	7.0	B	D	72	B
225/45R17 XL		94	V	7 1/2J	670	290	634	225	7.0	C	D	72	B
225/50R17 XL		98	V	7J	750	290	658	233	7.0	B	D	72	B
225/55R17 XL		101	V	7J	825	290	680	233	7.0	B	D	72	B
225/60R17 XL		103	V	6 1/2J	875	290	702	228	6.7	C	D	72	B
225/65R17		102	H	6 1/2J	850	250	724	228	6.7	C	D	72	B
235/45R17 XL		97	V	8J	730	290	644	236	6.7	C	C	72	B
235/55R17 XL		103	V	7 1/2J	875	290	690	245	6.7	C	C	72	B
18	235/65R17 XL	108	V	7J	1000	290	738	240	6.7	B	C	72	B
	245/45R17 XL	99	V	8J	775	290	652	243	6.7	C	C	72	B
	215/55R18 XL	99	V	7J	775	290	693	226	6.7	C	D	72	B
	225/40R18 XL	92	V	8J	630	290	637	230	6.7	C	D	72	B
	225/45R18 XL	95	V	7 1/2J	690	290	659	225	6.7	C	D	72	B
19	245/40R18 XL	97	V	8 1/2J	730	290	653	248	7.0	C	C	72	B
	225/35R19 XL	88	V	8J	560	290	641	230	6.7	C	D	72	B
	235/35R19 XL	91	V	8 1/2J	615	290	647	241	6.7	C	C	72	B

SUV



GRIP MASTER C/S



GREEN-Max 4x4 HP



CROSSWIND H/T



CROSSWIND A/T¹⁰⁰



CROSSWIND MT



RADIAL620

THE WORLD AT YOUR REACH





GRIP MASTER C/S

NEW
SUV TYRE



Good Handling and Comfortable Performance.

Excellent grip and handling performance;

Comfortable and quiet ride;

Superior wet grip and safety.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
										RR Level	WG Level	PASS BY NOISE			
										dB	Level				
15	205/70R15	96	H	6J	710	250	669	209	8.0	D	A	68	A		
	★ 215/70R15	98	H	6 1/2J	750	250	683	221	8.0	D	A	68	A		
	215/65R16 XL	102	H	6 1/2J	850	290	686	221	8.0	C	A	72	B		
	215/70R16	100	H	6 1/2J	800	250	708	221	8.0	C	A	68	A		
	225/65R16	100	H	6 1/2J	800	250	698	228	8.0	C	A	68	A		
	225/70R16	103	H	6 1/2J	875	250	722	228	8.0	C	A	68	A		
	235/60R16	100	H	7J	800	250	688	240	8.0	C	A	71	B		
	★ 225/75R16	104	H	6J	900	250	744	223	8.0	C	A	68	A		
	★ 235/70R16	106	H	7J	950	250	736	240	8.0	C	A	71	B		
	★ 245/70R16 XL	111	H	7J	1090	290	750	248	8.0	C	A	72	B		
16	★ 255/70R16	111	H	7 1/2J	1090	250	764	260	8.0	C	A	72	B		
	★ 265/70R16	112	H	8J	1120	250	778	272	8.0	C	A	72	B		
	★ 275/70R16	114	H	8J	1180	250	792	279	8.0	C	A	72	B		

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
										RR Level	WG Level	PASS BY NOISE			
										dB	Level				
17	215/55R17 XL	98	V	7J	750	290	668	226	8.0	C	A	72	B		
	215/60R17	96	H	6 1/2J	710	250	690	221	8.0	C	A	71	B		
	225/55R17 XL	101	V	7J	825	290	680	233	8.0	C	A	72	B		
	225/65R17 XL	106	V	6 1/2J	950	290	724	228	8.0	C	A	69	A		
	235/65R17 XL	108	V	7J	1000	290	738	240	8.0	B	A	72	B		
	245/65R17 XL	111	H	7J	1090	290	750	248	8.0	C	A	72	B		
	255/60R17	106	H	7 1/2J	950	250	738	260	8.0	C	A	72	B		
	255/65R17	110	H	7 1/2J	1060	250	764	260	8.0	C	A	72	B		
	275/55R17	109	V	8 1/2J	1030	290	734	284	7.7	C	A	72	B		
	★ 215/65R17 XL	103	V	6 1/2J	875	290	712	221	7.5	C	A	69	A		
18	★ 235/60R17 XL	106	V	7J	950	250	714	240	6.8	C	A	72	B		
	★ 265/65R17	112	H	8J	1120	250	776	272	8.0	C	A	72	B		
	215/55R18 XL	99	V	7J	775	290	693	226	7.7	C	A	69	A		
	225/55R18	98	V	7J	750	250	705	233	7.5	D	A	68	A		
	235/50R18	97	V	7 1/2J	730	250	693	245	8.0	C	A	68	A		
	235/55R18 XL	104	W	7 1/2J	900	290	715	245	6.6	C	A	72	B		
	235/60R18 XL	107	W	7J	975	290	739	240	7.7	C	A	72	B		
	255/60R18 XL	112	V	7 1/2J	1120	290	763	260	8.0	C	A	73	B		
	★ 215/50R18	92	W	7J	630	250	673	226	7.7	D	A	68	A		
	★ 225/50R18 XL	99	W	7J	775	290	683	233	7.7	C	A	69	A		
19	★ 225/60R18 XL	104	V	6 1/2J	900	290	727	228	7.5	C	A	69	A		
	★ 255/55R18 XL	109	Y	8J	1030	290	737	265	7.7	C	A	73	B		
	★ 265/60R18	110	V	8J	1060	250	775	272	7.7	C	A	72	B		
	★ 275/60R18	113	H	8J	1150	250	787	279	8.0	C	A	72	B		
	★ 285/60R18	116	V	8 1/2J	1250	250	799	292	8.0	C	A	74	B		
	205/55R19 XL	97	V	6 1/2J	730	290	709	214	7.7	C	A	69	A		
	225/55R19	99	V	7J	775	250	731	233	7.5	C	A	68	A		
	235/45R19 XL	99	V	8J	775	290	695	236	7.7	C	A	72	B		
	235/55R19 XL	105	W	7 1/2J	925	290	741	245	7.7	C	A	72	B		
	285/45R19 XL	111	W	9 1/2J	1090	290	739	285	7.7	C	A	75	B		
20	★ 255/40R19 XL	100	W	9J	800	290	687	260	7.7	C	A	73	B		
	★ 255/45R19 XL	104	W	8 1/2J	900	290	713	255	7.7	C	A	73	B		
	★ 255/50R19 XL	107	W	8J	975	290	739	265	7.7	C	A	73	B		
	★ 255/55R19 XL	111	W	8J	1090	290	763	265	7.7	C	A	73	B		
	★ 265/50R19 XL	110	Y	8 1/2J	1060	290	749	277	7.7	C	A	73	B		
	245/45R20 XL	103	W	8J	875	290	728	243	7.7	C	A	72	B		
	255/40R20 XL	101	W	9J	825	290	712	260	7.7	C	A	73	B		
	255/45R20 XL	105	Y	8 1/2J	925	290	738	255	7.7	C	A	73	B		
	265/45R20 XL	108	Y	9J	1000	290	771	266	7.7	C	A	73	B		
	265/50R20 XL	111	W	8 1/2J	1090	290	774	277	7.7	C	A	73	B		
21	275/40R20 XL	106	V	9 1/2J	950	290	728	279	7.7	C	A	73	B		
	315/35R20 XL	110	Y	11J	1060	290	728	320	7.7	C	A	72	A		
	★ 195/55R20 XL	95	H	6J	690	290	722	201	7.7	C	A	69	A		
	★ 235/45R20 XL	100	W	8J	800	290	720	236	7.7	C	A	72	B		
	★ 275/45R20 XL	110	W	9J	1060	290	756	273	7.7	C	A	73	B		
	245/40R21 XL	100	W	8 1/2J	800	290	729	248	7.7	C	A	72	B		
	255/40R21 XL	102	W	9J	850	290	737	260	7.7	C	A	73	B		
275/45R21 XL	110	W	9J	1060	290	781	273	7.7	C	A	73	B			

Notes: ★ under development

GREEN-Max 4x4 HP

SUV tires for urban highway use,
with good handling and low noise.

Excellent handling performance;

Enhanced drainage performance to
effectively reduce risk of hydroplaning;

Superior longitudinal stability for more
comfortable ride;

Low noise to offer a quiet ride.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
15	205/70R15	96	H	6 1/2J	710	250	669	209	8.8	D	C	71	B
	215/65R16 XL	102	H	6 1/2J	850	290	686	221	8.8	D	C	72	B
	215/70R16	100	H	6 1/2J	800	250	708	221	8.8	D	C	71	B
	225/65R16	100	H	6 1/2J	800	250	698	228	8.8	D	C	71	B
	225/75R16	104	H	6J	900	250	744	223	8.8	D	C	71	B
	235/60R16	100	H	7J	800	250	688	240	8.8	D	C	71	B
	235/70R16	106	H	7J	950	250	736	240	8.8	D	C	71	B
16	245/70R16 XL	111	H	7J	1090	290	750	248	8.8	C	C	72	B
	265/70R16	112	H	8J	1120	250	778	272	8.8	D	C	72	B
	275/70R16	114	H	8J	1180	250	792	279	8.8	D	C	72	B
	215/60R17	96	H	6 1/2J	710	250	690	221	8.8	D	C	71	B
	215/65R17 XL	103	V	6 1/2J	875	290	712	221	7.5	C	C	72	B
	225/55R17 XL	101	V	7J	825	290	680	233	8.5	D	C	72	B
	225/60R17	99	V	6 1/2J	775	250	702	228	7.7	C	C	71	B
	225/65R17	102	H	6 1/2J	850	250	724	228	8.8	D	C	71	B
	235/55R17 XL	103	V	7 1/2J	875	290	690	245	8.5	D	C	72	B
	235/60R17 XL	106	V	7J	950	290	714	240	8.8	D	C	72	B
	235/65R17 XL	108	V	7J	1000	290	738	240	8.8	C	C	72	B
	245/65R17 XL	111	H	7J	1090	290	750	248	8.8	D	C	72	B
	17	255/60R17	106	H	7 1/2J	950	250	738	260	8.8	C	C	72
255/65R17		110	H	7 1/2J	1060	250	764	260	8.8	D	C	72	B
265/65R17		112	H	8J	1120	250	776	272	8.8	C	C	72	B
275/55R17		109	V	8 1/2J	1030	250	734	284	8.8	D	C	72	B
215/55R18 XL		99	V	7J	775	290	693	226	7.7	C	C	72	B
225/55R18		98	V	7J	750	250	705	233	7.7	C	C	71	B
225/60R18		100	H	6 1/2J	800	250	727	228	8.8	D	C	71	B
235/50R18		97	V	7 1/2J	730	250	693	245	8.1	D	C	71	B
235/55R18 XL		104	V	7 1/2J	900	290	715	245	8.5	C	C	72	B
235/60R18 XL		107	V	7J	975	290	739	240	8.8	D	C	72	B
255/55R18 XL		109	V	8J	1030	290	737	265	8.5	C	C	73	B
255/60R18 XL		112	V	7 1/2J	1120	290	763	260	8.8	C	C	73	B
265/60R18		110	H	8J	1060	250	775	272	7.5	C	C	72	B
275/60R18	113	H	8J	1150	250	787	279	8.8	D	C	72	B	
18	225/55R19	99	V	7J	775	250	731	233	8	C	C	71	B
	255/50R19 XL	107	W	8J	975	290	739	265	8.1	C	C	73	B
	255/55R19 XL	111	V	8J	1090	290	763	265	8.5	D	C	73	B
	265/50R19 XL	110	W	8 1/2J	1060	290	749	277	7.5	C	C	73	B
19	265/50R20 XL	111	V	8 1/2J	1090	290	774	277	7.5	D	C	73	B
	275/40R20 XL	106	V	9 1/2J	950	290	728	278	8.1	C	C	73	B
	275/45R20 XL	110	V	9J	1060	290	756	273	8.1	C	C	73	B
20	315/35R20 XL	110	W	11J	1060	290	728	320	8	C	B	75	B
	295/35R21 XL	107	W	10 1/2J	975	290	739	301	8	C	C	75	B
	275/40R22 XL	107	W	9 1/2J	975	290	779	278	8	C	C	73	B
22	285/35R22 XL	106	V	10J	950	290	759	290	8.1	C	D	75	B



CROSSWIND H/T

SUV Tire for Urban Road Use, with Low Noise and good dry/wet performance.

High drainage capability;

High comfort and low noise;

Excellent handling performance.



CROSSWIND A/T¹⁰⁰

Low noise all-weather tire.

All Weather Capability;

Comfortable Quiet Ride;

Excellent Snow and Wet Braking;

Off-Road Traction.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
												dB	Level
15	235/75R15 XL	109	T	6 1/2J	1030	290	733	235	9.7	D	D	72	B
	235/70R16	106	T	7J	950	250	736	240	9.5	D	D	71	B
	245/70R16	107	T	7J	975	250	750	248	9.7	D	D	71	B
16	245/75R16	111	T	7J	1090	250	774	248	9.7	D	D	71	B
	255/70R16	111	T	7 1/2J	1090	250	764	260	9.7	D	D	72	B
	265/75R16	116	T	7 1/2J	1250	250	804	267	9.7	D	D	72	B
	235/65R17	104	T	7J	900	250	738	240	9.7	D	D	71	B
17	245/65R17	107	T	7J	975	250	750	248	9.7	D	D	71	B
	245/70R17	110	T	7J	1060	250	776	248	9.7	D	D	71	B
	265/65R17	112	T	8J	1120	250	776	272	9.7	D	D	72	B
	265/70R17	115	T	8J	1215	250	804	272	10.5	D	D	72	B

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
											RR Level	WG Level	PASS BY NOISE	
												dB	Level	
15	205/70R15	/	96	T	6J	710	250	669	209	8.7	D	C	72	B
	235/75R15 XL	/	109	T	6 1/2J	1030	290	733	235	8.7	C	C	72	B
	255/70R15	/	108	T	7 1/2J	1000	250	739	260	8.7	C	C	73	B
	265/70R15	/	112	T	8J	1120	250	753	272	9.2	D	C	73	B
	31X10.50R15LT	6PR	109	R	8 1/2J	1030	350	775	268	11	D	B	73	B
	LT215/75R15	6PR	100/97	S	6J	D 730S 800	350	703	216	9.5	D	C	73	B
	LT225/75R15	6PR	102/99	S	6J	D 775S 850	350	719	223	9.5	D	C	73	B
	LT235/75R15	6PR	104/101	S	6 1/2J	D 825 S 900	350	733	235	9.5	D	C	73	B
	235/70R16	/	106	T	7J	950	250	736	240	8.7	D	C	72	B
16	245/70R16 XL	/	111	T	7J	1090	290	750	248	8.7	C	C	72	B
	205R16LT	8PR	110/108	Q	6J	D1000S1060	450	734	208	9.5	D	C	73	B
	LT225/75R16	10PR	115/112	Q	6J	D1120S1215	550	744	223	9.5	D	C	73	B
17	245/65R17 XL	/	111	T	7J	1090	290	750	248	8.7	C	C	72	B
	265/65R17	/	112	T	8J	1120	250	776	272	9.2	C	C	73	B

CROSSWIND MT

Mud-Terrain Tire

High floatation;

Higher load-carrying capacity;

Excellent Self-cleaning performance;

Aggressive tread pattern and sidewall design.



RADIAL 620

All Terrain Tire.

Excellent wet performance;

An optimal balance between performance
on road and off road.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	
15	30X9.50R15LT	6PR	104	Q	7 1/2J	900	350	756	240	13.5	
	31X10.50R15LT	6PR	109	Q	8 1/2J	1030	350	781	268	14.5	
	33X12.50R15LT	6PR	108	Q	10J	1000	250	832	318	14.5	
	LT215/75R15	6PR	100/97	Q	6J	D 730S 800	350	709	216	13.5	
16	LT235/75R15	6PR	104/101	Q	6 1/2J	D 825S 900	350	739	235	13.5	
	205R16LT	8PR	110/108	Q	6J	D 1000S 1060	450	740	208	14.5	
	LT225/75R16	8PR	110/107	Q	6J	D 975S 1060	450	750	223	13.5	
	LT235/70R16	8PR	110/107	Q	7J	D 975S 1060	450	742	240	13.5	
	LT235/85R16	10PR	120/116	Q	6 1/2J	D 1260S 1380	550	806	235	13.5	
	LT245/75R16	10PR	120/116	Q	7J	D 1260S 1380	550	774	248	13.5	
	LT255/70R16	8PR	115/112	Q	7 1/2J	D 1120S 1215	450	770	260	14.5	
	LT265/70R16	6PR	110/107	Q	8J	D 975S 1060	350	784	272	14.5	
	LT265/75R16	10PR	123/120	Q	7 1/2J	D 1400S 1550	550	810	267	14.5	
	LT285/75R16	6PR	116/113	Q	8J	D 1150S 1250	350	840	286	14.5	
	LT285/75R16	10PR	126/123	Q	8J	D 1550S 1700	550	840	286	14.5	
	LT305/70R16	8PR	118/115	Q	9J	D 1215S 1320	350	840	311	14.5	
	LT315/75R16	8PR	121/118	Q	8 1/2J	D 1320S 1450	350	884	313	14.4	
	LT315/75R16	10PR	127/124	Q	10J	D 1600S 1750	450	884	313	14.4	
	17	LT265/70R17	10PR	121/118	Q	8J	D 1320S 1450	550	810	272	14.5
		LT285/70R17	8PR	121/118	Q	8 1/2J	D 1320S 1450	450	838	292	14.5
LT305/70R17		8PR	119/116	Q	9J	D 1250S 1360	350	866	311	14.5	
35X12.50R17LT		10PR	121	Q	10J	1450	450	883	318	14.5	
18	33X12.50R18LT	10PR	118	Q	10J	1320	450	832	318	14.5	

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
											RR Level	WG Level	PASS BY NOISE dB	Level
14	185R14C	8PR	102/100	Q	5 1/2J	D 800S 850	450	652	189	8.5	D	C	72	B
	195R14C	8PR	106/104	Q	5 1/2J	D 875S 925	450	668	196	8.7	D	B	72	B
15	265/70R15	/	112	T	8J	1120	250	753	272	10.2	D	C	72	B
16	205/80R16 XL	/	104	T	5 1/2J	900	280	734	203	8.0	D	C	72	B
	215/65R16	/	98	H	6 1/2J	750	250	686	221	10.2	D	C	71	B
	215/70R16	/	100	T	6 1/2J	800	250	708	221	8.0	D	C	71	B
	235/70R16	/	106	T	7J	950	250	736	240	10.2	D	C	71	B
	245/70R16	/	107	H	7J	975	250	750	248	10.2	D	C	71	B
	265/70R16	/	112	H	8J	1120	250	778	272	10.2	D	C	72	B
17	235/65R17 XL	/	108	H	7J	1000	290	738	240	10.2	D	C	72	B
	275/55R17	/	109	V	8 1/2J	1030	250	734	284	10.2	D	C	72	B

LT



RADIAL R701



GREEN-Max Van



GREEN-Max Van HP



RADIAL666



GREEN-Max Van 4S

THE WORLD AT YOUR REACH



RADIAL R701

Budget Tire.

Low fuel consumption;

Budget Tires.



GREEN-Max Van

Commercial tire with high grip performance.

Better grip performance;

Low rolling resistance for high energy efficiency.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details								
											RR Level	WG Level	PASS BY NOISE						
											dB	Level							
10	195/55R10C	/	98/96	N	6J	D 710S 750	625	468	201	6.5	/	/	/	/	/				
12	155/70R12C	/	100/98	N	4 1/2J	D 750S 800	650	523	157	6.5	D	D	71	B					
	155/70R12C	/	104/102	N	4 1/2J	D 850S 900	625	523	157	6.5	D	D	72	B					
	185/60R12C	/	104/101	N	5 1/2J	D 825S 900	650	527	189	6.5	D	D	71	B					
	195/60R12C	/	104/102	N	6J	D 850S 900	650	539	202	6.5	D	D	71	B					
	135/80R13 XL	/	74	N	3.50B	375	280	546	133	6.2	D	D	71	B					
13	145/70R13	/	74	N	4.50J	345	250	534	150	6.2	D	D	70	B					
	145/80R13 XL	/	79	N	4.00B	437	280	562	145	6.2	D	D	71	B					
	155/70R13	/	75	N	4.50B	387	250	548	157	6.2	D	D	70	B					
	155/80R13 XL	/	84	N	4.50B	500	280	578	157	6.2	D	D	70	B					
	165/65R13	/	77	N	5.00B	412	250	544	170	6.2	D	D	70	B					
	165/70R13	/	79	N	5.00B	437	250	562	170	6.2	D	D	70	B					
	175/70R13 XL	/	86	N	5.00B	530	290	576	177	6.2	D	D	70	B					
	185/70R13	/	86	N	5 1/2J	530	250	590	189	6.2	D	D	70	B					
	165R13C	8PR	94/92	N	4 1/2J	D 630S 670	450	596	167	6.5	D	D	71	B					
	165R13C	8PR	96/94	N	4 1/2J	D 670S 710	450	596	167	6.5	C	D	72	B					
	185/70R13C	/	106/104	N	5 1/2J	D 900S 950	600	590	189	6	C	D	72	B					
195/50R13C	/	104/101	N	6J	D 825S 900	650	526	201	6.5	D	D	71	B						
14	195/70R14 XL	/	96	N	6J	710	290	630	201	6.2	C	C	72	B					
	185R14C	8PR	102/100	N	5 1/2J	D 800S 850	450	650	188	6.5	D	D	71	B					
	185R14C	/	104/102	N	5 1/2J	D 850S 900	500	650	188	6.5	D	D	72	B					
	195R14C	8PR	106/104	N	5J	D 900S 950	450	666	198	6.5	D	D	72	B					

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details							
											RR Level	WG Level	PASS BY NOISE					
											dB	Level						
12	5.00R12LT	10PR	88/86	P	3.50B	D 530S 560	550	568	143	7.5	D	C	72	B				
	155R12C	8PR	88/86	N	4.50B	D 530S 560	450	553	157	7.8	D	C	72	B				
13	155R13C	8PR	91/89	P	4 1/2J	D 580S 615	450	578	157	7.8	D	C	72	B				
	175R13C	8PR	97/95	Q	5.00B	D 690S 730	450	610	177	8.1	D	C	72	B				
14	165/70R14C	6PR	89/87	R	5J	D 545S 580	375	588	170	7.8	D	C	72	B				
	175/70R14C	6PR	95/93	T	5J	D 650S 690	375	602	177	7.8	D	C	72	B				
	185R14C	8PR	102/100	R	5 1/2J	D 800 S 850	450	650	188	8.5	D	C	72	B				
	195R14C	8PR	106/104	P	5 1/2J	D 900 S 950	450	666	198	8.7	D	B	72	B				
	205R14C	8PR	109/107	R	6J	D 975 S 1030	450	686	208	9.1	C	B	72	B				
	215R14C	8PR	112/110	R	6J	D 1060S 1120	450	700	216	9	C	B	72	B				
	195/70R15C	8PR	104/102	R	6J	D 850 S 900	450	655	201	9.6	D	B	72	B				
15	205/70R15C	8PR	106/104	S	6J	D 900 S 950	450	669	209	9.1	D	B	72	B				
	175/70R15C	8PR	109/107	R	6 1/2J	D 975 S 1030	450	683	221	9	C	B	72	B				
	225/70R15C	8PR	106/103	R	6 1/2J	D 875S 950	450	697	228	9.5	C	B	72	B				
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	450	697	228	9.6	C	B	72	B				
	255/70R15C	6PR	112/110	S	7 1/2J	D 1060S 1120	375	739	260	9.5	C	B	72	B				
16	185/75R16C	8PR	104/102	R	5J	D 850 S 900	475	684	184	9.1	D	C	72	B				
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	475	698	196	9.6	D	B	72	B				
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000S 1060	475	714	203	9.1	C	B	72	B				
	215/70R16C	6PR	108/106	T	6 1/2J	D 950S 1000	375	708	221	9.1	D	B	72	B				
	215/75R16C	8PR	113/111	R	6J	D 1090S 1150	475	728	216	9.6	C	B	72	B				
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	575	744	223	9.6	C	B	72	B				



GREEN-Max Van HP



Commercial tire with high grip performance.

Excellent stability;

Great grip performance and driving force of turning;

Low rolling resistance for higher energy efficiency.

RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
											RR Level	WG Level	PASS BY NOISE			
											dB	Level				
14	175/65R14C	6PR	90/88	T	5J	D 560S 600	375	584	177	7.5	D	C	72	B		
15	215/65R15C	6PR	104/102	T	6 1/2J	D 850S 900	375	661	221	9	D	C	72	B		
16	195/65R16C	8PR	104/102	R	6J	D 850 S 900	475	660	201	8.8	C	C	72	B		
	205/65R16C	8PR	107/105	R	6J	D 925 S 975	475	672	209	9	C	C	72	B		
	215/60R16C	6PR	103/101	T	6 1/2J	D 825S 875	375	664	221	9	C	C	72	B		
	215/65R16C	8PR	109/107	R	6 1/2J	D 975S1030	475	686	221	9	C	B	72	B		
	225/65R16C	8PR	112/110	R	6 1/2J	D1060S1120	475	698	228	9	C	B	72	B		
16	235/65R16C	8PR	115/113	R	7J	D1150S1215	475	712	240	9	C	B	72	B		

RADIAL666

Commercial tire with Excellent wear and wet performance.

Excellent traction;

Excellent wet braking;

High wear resistance.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (Kpa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details					
											RR Level	WG Level	PASS BY NOISE			
											dB	Level				
14	185R14C	8PR	102/100	R/Q	5 1/2J	D 800S 850	450	652	189	9.3	D	C	72	B		
	195/75R14C	8PR	106/104	R	5 1/2J	D 900S 950	475	648	196	9.5	D	C	72	B		
	215R14C	8PR	110/108	R	6J	D 1000S 1060	450	700	218	9.5	D	C	72	B		
	215/75R14C	8PR	112/110	R	6J	D 1060S 1120	475	678	216	9.5	D	C	72	B		
15	195/70R15C	8PR	104/102	R	6J	D 850S 900	450	655	201	10	D	C	72	B		
	205/70R15C	8PR	106/104	S	6J	D 900S 950	450	669	209	9	C	C	72	B		
	215/70R15C	8PR	109/107	R	6 1/2J	D 975S 1030	450	683	221	9.5	D	C	72	B		
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060S 1120	450	697	228	9	D	C	72	B		
16	175/75R16C	8PR	101/99	R	5J	D 775S 825	475	668	177	8.1	D	C	72	B		
	185/75R16C	8PR	104/102	R	5J	D 850S 900	475	684	184	8.1	D	C	72	B		
	195/65R16C	8PR	104/102	R	6J	D 850S 900	475	660	201	9	D	C	72	B		
	195/75R16C	8PR	107/105	R	5 1/2J	D 925S 975	475	698	196	9.5	D	C	72	B		
	205/65R16C	8PR	107/105	R	6J	D 925S 975	475	672	209	9	D	C	72	B		
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000S 1060	475	714	203	9	D	C	72	B		
	215/65R16C	8PR	109/107	R	6 1/2J	D 975S 1030	475	686	221	9	D	C	72	B		
	215/75R16C	8PR	113/111	R	6J	D 1090S 1150	475	728	216	9	D	C	72	B		
	225/65R16C	8PR	112/110	R	6 1/2J	D 1060S 1120	475	698	228	9.1	D	C	72	B		
	225/75R16C	10PR	121/120	R	6J	D 1400S 1450	575	744	223	9	D	C	72	B		
16	235/65R16C	8PR	115/113	R	7J	D 1150S 1215	475	712	240	9	D	C	72	B		

GREEN-Max Van 4S

For all season commercial.

Various design of the 3D sipe, Optimization tread pattern stiffness distribution, The tire have good wet&ice road grip performance;

Application of spring hole, product with Excellent appearance.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
											RR Level	WG Level	PASS BY NOISE dB	Level
14	165/70R14C	6PR	89/87	R	5J	D 545 S 580	375	588	170	7.5	D	B	73	B
	175/65R14C	6PR	90/88	T	5J	D 560 S 600	375	584	177	7.5	D	B	73	B
	175/70R14C	6PR	95/93	T	5J	D 650 S 690	375	602	177	7.5	D	B	73	B
15	195/70R15C	8PR	104/102	R	6J	D 850 S 900	450	655	201	7.8	C	B	73	B
	205/70R15C	8PR	106/104	R	6J	D 900S 950	450	669	209	7.8	C	B	73	B
	215/70R15C	8PR	109/107	R	6 1/2J	D 975S 1030	450	683	221	7.8	C	B	73	B
	225/70R15C	8PR	112/110	S	6 1/2J	D 1060S 1120	450	697	228	7.8	C	B	73	B
16	185/75R16LT	8PR	104/102	R	5J	D 850 S 900	475	684	184	7.5	C	B	73	B
	195/60R16C	6PR	99/97	R	6J	D 730S 775	375	640	201	7.8	C	B	73	B
	195/65R16C	8PR	104/102	R	6J	D 850 S 900	475	660	201	7.8	C	B	73	B
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	475	698	196	7.8	C	B	73	B
	205/65R16C	8PR	107/105	T	6J	D 925S 975	475	672	209	7.8	C	B	73	B
	205/75R16C	8PR	110/108	T	5 1/2J	D 1000S 1060	475	714	203	7.8	C	B	73	B
	215/60R16LT	6PR	103/101	T	6 1/2J	D 825S 875	375	664	221	7.8	C	B	73	B
	215/65R16C	8PR	109/107	T	6 1/2J	D 975S 1030	475	686	221	7.8	C	B	73	B
	215/75R16C	8PR	113/111	R	6J	D 1090S 1150	475	728	216	7.8	C	B	73	B
	225/65R16C	8PR	112/110	S	6 1/2J	D 1060S 1120	475	698	228	7.8	C	B	73	B
17	225/75R16C	10PR	118/116	R	6J	D 1250S 1320	525	744	223	7.8	B	B	73	B
	235/65R16C	8PR	115/113	R	7J	D 1150S 1215	475	712	240	7.8	C	A	73	B
	215/60R17C	8PR	109/107	T	6 1/2J	D 975S 1030	475	690	221	7.8	C	B	73	B



GREEN-Max Winter HP



GREEN-Max Winter Van



GREEN-Max Winter UHP



NORD MASTER



GREEN-Max Winter Ice I-15



GREEN-Max Winter Ice I-15 SUV



GREEN-Max Winter GRIP 2



GREEN-Max Winter Grip



GREEN-Max Winter GRIP VAN 2



GREEN-Max Winter Grip SUV

GREEN-Max Winter HP

High performance snow tires with excellent braking performance.

Excellent snow braking performance;

Comfortably snow driving.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
13	155/70R13	75	T	4.50B	387	250	548	157	8.2	E	D	71	B
	155/80R13	79	T	4.50B	437	240	578	157	8.2	E	D	71	B
	165/70R13	79	T	5.00B	437	250	562	170	8.2	E	C	71	B
	175/70R13	82	T	5.00B	475	250	576	177	8.2	E	C	71	B
14	155/65R14	75	T	4 1/2J	387	250	558	157	8.2	E	D	71	B
	165/65R14	79	T	5J	437	250	570	170	8.2	E	C	71	B
	165/70R14	81	T	5J	462	250	588	170	8.2	E	C	71	B
	175/65R14 XL	86	H	5J	530	290	584	177	8.2	D	C	71	B
	175/70R14	84	T	5J	500	250	602	177	8.2	E	C	71	B
	185/60R14	82	T	5 1/2J	475	250	578	189	8.5	E	C	71	B
15	185/65R14	86	T	5 1/2J	530	250	596	189	8.5	D	C	71	B
	175/65R15 XL	88	H	5J	560	290	609	177	8.0	D	C	71	B
	185/60R15 XL	88	H	5 1/2J	560	290	603	189	8.5	D	C	71	B
	185/65R15 XL	92	H	5 1/2J	630	290	621	189	8.5	D	C	71	B
	195/60R15 XL	92	H	6J	630	290	615	201	8.5	D	C	72	B
	195/65R15 XL	95	T	6J	690	290	635	201	8.5	D	C	72	B
	205/65R15 XL	99	H	6J	775	290	647	209	8.5	D	C	72	B
	205/70R15	96	T	6J	710	250	669	209	8.5	D	C	72	B
16	205/55R16 XL	94	H	6 1/2J	670	290	632	214	8.5	D	C	72	B
	205/60R16 XL	96	H	6J	710	290	652	209	8.5	D	C	72	B
	215/55R16 XL	97	H	7J	730	290	642	226	8.5	D	C	72	B
	215/60R16 XL	99	H	6 1/2J	775	290	664	221	8.5	D	C	72	B
	215/65R16	98	H	6 1/2J	750	250	686	221	8.5	D	C	72	B

GREEN-Max Winter Van

Excellent snow traction performance.

Excellent snow traction performance;

Focus on driving safety of vehicles in winter.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
											RR Level	WG Level	PASS BY NOISE	
											dB	Level		
14	185R14C	8PR	102/100	Q	6J	D 800 S 850	450	652	189	9.6	D	B	73	B
	195R14C	8PR	106/104	P	5 1/2J	D 900 S 950	450	666	198	9.8	D	B	73	B
15	195/70R15C	8PR	104/102	R	6J	D 850 S 900	450	655	201	10	D	B	73	B
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	450	697	228	10	D	B	73	B
16	175/75R16C	8PR	101/99	R	5J	D 775 S 825	475	668	177	9.6	D	B	73	B
	185/75R16C	8PR	104/102	R	5J	D 850 S 900	475	684	184	9.6	D	B	73	B
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	475	698	196	10	D	B	73	B
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000 S 1060	475	714	203	10	D	B	73	B
	215/75R16C	8PR	113/111	R	6J	D 1090 S 1150	475	728	216	10	D	B	73	B
	225/65R16C	8PR	112/110	R	6 1/2J	D 1060 S 1120	475	698	228	9.8	D	B	73	B
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	575	744	223	10	D	B	73	B
235/65R16C	10PR	121/119	R	7J	D 1360 S 1450	575	712	240	9.8	D	B	73	B	



GREEN-Max Winter UHP

Ultra High performance snow tires with superior handling performance.

Excellent snow handling performance.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE dB	Level
15	185/55R15 XL	86	H	6j	530	290	585	194	8.3	D	C	71	B
	195/50R15	82	H	6j	475	250	577	201	8.3	D	C	72	B
	195/55R15	85	H	6j	515	250	595	201	8.6	D	C	72	B
16	195/55R16 XL	91	H	6j	615	290	620	201	8.6	D	C	72	B
	225/55R16 XL	99	H	7j	775	290	654	233	8.6	C	C	72	B
	225/60R16 XL	102	H	6 1/2j	850	290	676	228	8.6	C	C	72	B
17	205/45R17 XL	88	V	7j	560	290	616	206	8.6	D	C	72	B
	205/50R17 XL	93	V	6 1/2j	650	290	638	214	8.6	C	C	72	B
	215/45R17 XL	91	V	7j	615	290	626	213	8.6	D	C	72	B
	215/50R17 XL	95	V	7j	690	290	648	226	8.6	D	C	72	B
	215/55R17	94	V	7j	670	250	668	226	8.6	D	C	72	B
	215/60R17	96	H	6 1/2j	710	250	690	221	8.6	C	C	72	B
	225/45R17 XL	94	V	7 1/2j	670	290	634	225	8.6	D	C	72	B
	225/50R17 XL	98	V	7j	750	290	658	233	8.6	D	C	72	B
	225/55R17 XL	101	V	7j	825	290	680	233	8.6	C	C	72	B
	235/45R17 XL	97	H	8j	730	290	644	236	8.6	C	C	72	B
	235/55R17 XL	103	V	7 1/2j	875	290	690	245	8.6	C	C	72	B
	18	225/40R18 XL	92	V	8j	630	290	637	230	8.6	D	C	72
225/45R18 XL		95	H	7 1/2j	690	290	659	225	8.6	D	C	72	B
235/45R18 XL		98	V	8j	750	290	669	236	8.6	D	C	72	B
235/55R18 XL		104	H	7 1/2j	900	290	715	245	8.6	C	C	72	B
235/60R18 XL		107	H	7j	975	290	739	240	8.6	C	C	72	B
245/40R18 XL		97	V	8 1/2j	730	290	653	248	8.6	D	C	72	B
245/45R18 XL		100	H	8j	800	290	677	243	8.6	C	C	72	B
19	235/55R19 XL	105	V	7 1/2j	925	290	741	245	8.1	B	C	72	B
	245/40R19 XL	98	V	8 1/2j	750	290	679	248	8.1	C	C	72	B
	245/45R19 XL	102	V	8j	850	290	703	243	8.1	C	C	72	B
	255/35R19 XL	96	V	9j	710	290	661	260	8.1	C	C	73	B
	255/40R19 XL	100	V	9j	800	290	687	260	8.1	C	C	73	B
	255/45R19 XL	104	H	8 1/2j	900	290	713	255	8.6	C	C	73	B
	255/50R19 XL	107	V	8j	975	290	739	265	8.1	B	C	73	B
20	255/55R19 XL	111	H	8j	1090	290	763	265	8.6	C	C	73	B
	275/40R19 XL	105	V	9 1/2j	925	290	703	278	8.1	C	C	73	B
	245/45R20 XL	103	H	8j	875	290	728	243	8.6	C	C	72	B
	255/35R20 XL	97	V	9j	730	290	686	260	8.1	C	C	73	B
	275/40R20 XL	106	V	9 1/2j	950	290	728	278	8.1	C	C	73	B
	275/45R20 XL	110	H	9j	1060	290	756	273	8.6	C	C	73	B
	315/35R20 XL	110	V	11j	1060	290	728	320	8.1	C	C	75	B

NORD MASTER

Excellent snow handling and ice braking&acceleration

Directional grooves design for evacuate snow and mud;

Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
14	185/65R14 XL	90	T	5 1/2J	600	290	596	189	8.1
	*185/65R15 XL	92	T	5 1/2J	630	290	621	189	8.1
15	*195/65R15 XL	95	T	6J	690	290	635	201	8.1
	205/55R16 XL	94	T	6 1/2J	670	290	632	214	8.1
16	205/60R16 XL	96	T	6J	710	290	652	209	8.1
	215/65R16 XL	102	T	6 1/2J	850	290	686	221	8.1
	205/40R17 XL	84	T	7 1/2J	500	290	596	212	8.1
17	215/55R17 XL	98	T	7J	750	290	668	226	8.1
	225/55R17 XL	101	T	7J	825	290	680	233	8.1
	*205/45R17 XL	88	T	7J	560	290	616	206	8.1
	*205/55R17 XL	95	T	6 1/2J	690	290	658	214	8.1
	*215/40R17 XL	87	T	7 1/2J	545	290	604	218	8.1
	*215/50R17 XL	95	T	7J	690	290	648	226	8.1
	*225/45R17 XL	94	T	7 1/2J	670	290	634	225	8.1
	*225/50R17 XL	98	T	7J	750	290	658	233	8.1
	*245/40R17 XL	95	T	8 1/2J	690	290	628	248	8.1
	225/45R18 XL	95	T	7 1/2J	690	290	659	225	8.1
18	255/35R18 XL	94	T	9J	670	290	635	260	8.1
	265/35R18 XL	97	T	9 1/2J	730	290	643	271	8.7
	*215/40R18 XL	89	T	7 1/2J	580	290	629	218	8.1
	*225/40R18 XL	92	T	8J	630	290	637	230	8.1
19	*235/45R18 XL	98	T	8J	750	290	669	236	8.1
	225/35R19 XL	88	T	8J	560	290	641	230	8.1
	235/35R19 XL	91	T	8 1/2J	615	290	647	241	8.1
	255/35R19 XL	96	T	9J	710	290	661	260	8.1
	*215/35R19 XL	85	T	7 1/2J	515	290	633	218	8.1
	*225/45R19 XL	96	T	7 1/2J	710	290	685	225	8.1
	*245/35R19 XL	93	T	8 1/2J	650	290	655	248	8.1
	*245/40R19 XL	98	T	8 1/2J	750	290	679	248	8.1
20	*235/35R20 XL	92	T	8 1/2J	630	290	672	241	8.1
	*255/35R20 XL	97	T	9J	730	290	686	260	8.1
	*275/35R20 XL	102	T	9 1/2J	850	290	700	278	8.7
	*275/50R20 XL	113	T	8 1/2J	1150	290	784	284	8.7

Notes: * under development



GREEN-Max Winter Ice I-15

Outstanding handling performance.

Direction tread pattern design providing excellent handling performance;

Directional grooves to help evacuate snow and mud.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
14	175/65R14 XL	86	T	5J	530	290	584	177	8.7	D	E	70	B
	185/60R15 XL	88	T	5 1/2J	560	290	603	189	8.7	D	E	70	B
15	185/65R15 XL	92	T	5 1/2J	630	290	621	189	8.7	D	E	70	B
	195/65R15 XL	95	T	6J	690	290	635	201	8.7	D	E	71	B
	195/55R16 XL	91	T	6J	615	290	620	201	8.7	D	E	71	B
16	205/55R16 XL	94	T	6 1/2J	670	290	632	214	8.7	D	E	71	B
	205/60R16 XL	96	T	6J	710	290	652	209	8.7	D	E	71	B
	215/55R16 XL	97	T	7J	730	290	642	226	8.7	C	D	72	B
	215/60R16 XL	99	T	6 1/2J	775	290	664	221	8.7	C	D	72	B
	215/65R16 XL	102	T	6 1/2J	850	290	686	221	8.7	C	D	72	B
	225/55R16 XL	99	T	7J	775	290	654	233	8.7	C	D	72	B
17	205/50R17 XL	93	T	6 1/2J	650	290	638	223	8.7	D	E	71	B
	225/45R17 XL	94	T	7 1/2J	670	290	634	225	8.7	D	D	72	B
	225/50R17 XL	98	T	7J	750	290	658	233	8.7	D	D	72	B
	225/55R17 XL	101	T	7J	825	290	680	233	8.7	C	D	72	B
	235/45R17 XL	97	T	8J	730	290	644	236	8.7	C	D	72	B

GREEN-Max Winter Ice I-15 SUV

Outstanding handling performance.

Directional grooves design for evacuate snow and mud;

Complex soft tread compound and 3D sipes technology to promote handling performance on ice and snow condition.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
15	205/70R15	96	T	6J	710	250	669	209	9.7	D	D	72	B
	215/75R15	100	T	6J	800	250	703	216	9.7	D	D	72	B
	235/75R15	105	T	6 1/2J	925	250	733	235	9.7	D	D	72	B
16	215/65R16	98	T	6 1/2J	750	250	686	221	9.7	D	D	72	B
	225/60R16	98	T	6 1/2J	750	250	676	228	9.7	D	D	72	B
	235/70R16	106	T	7J	950	250	736	240	9.7	D	D	72	B
	245/70R16	107	H	7J	975	250	750	248	9.7	D	D	72	B
	275/70R16	114	T	8J	1180	250	792	279	9.7	D	D	73	B
17	215/60R17	96	T	6 1/2J	710	250	690	221	9.7	D	D	72	B
	225/60R17	99	T	6 1/2J	775	250	702	228	9.7	D	D	72	B
	225/65R17	102	T	6 1/2J	850	250	724	228	9.7	D	D	72	B
	225/65R17 XL	106	T	6 1/2J	950	290	724	228	9.7	C	D	72	B
	235/50R17	96	T	7 1/2J	710	250	668	245	9.7	D	D	72	B
	235/55R17	99	T	7 1/2J	775	250	690	245	9.7	D	D	72	B
	235/65R17 XL	108	T	7J	1000	290	738	240	10	D	D	72	B
	245/45R17	95	T	8J	690	250	652	243	9.7	D	D	72	B
	245/50R17	107	T	7J	975	250	750	248	9.7	C	D	72	B
	255/45R17	98	T	8 1/2J	750	250	662	255	9.7	D	D	73	B
	255/60R17	106	T	7 1/2J	950	250	738	260	9.7	D	D	73	B
18	265/65R17	112	T	8J	1120	250	776	272	9.7	C	D	73	B
	275/65R17	115	T	8J	1215	250	790	279	9.7	C	D	73	B
	225/50R18	95	T	7J	690	250	683	233	9.7	D	D	72	B
	225/55R18	98	T	7J	750	250	705	233	9.7	D	D	72	B
	225/60R18	100	T	6 1/2J	800	250	727	228	9.7	D	D	72	B
	235/50R18	97	T	7 1/2J	730	250	693	245	9.7	D	D	72	B
	235/55R18	100	T	7 1/2J	800	250	715	245	9.7	D	D	72	B

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
											dB	Level	
18	235/60R18	103	T	7J	875	250	739	240	9.7	C	D	72	B
	235/60R18 XL	107	T	7J	975	290	739	240	9.7	C	D	72	B
	235/65R18	106	T	7J	950	250	763	240	9.7	D	D	72	B
	245/40R18	93	T	8 1/2J	650	250	653	248	9.7	D	D	72	B
	245/45R18	96	T	8J	710	250	677	243	9.7	D	D	72	B
	245/50R18	100	T	7 1/2J	800	250	703	253	9.7	D	D	72	B
	245/60R18	105	T	7J	925	250	751	248	9.7	C	D	72	B
	255/40R18	95	T	9J	690	250	661	260	9.7	D	D	73	B
	255/45R18	99	T	8 1/2J	775	250	687	255	9.7	D	D	73	B
	255/55R18	105	T	8J	925	250	737	265	9.7	C	D	73	B
	255/60R18 XL	112	H	7 1/2J	1120	290	763	260	9.7	D	D	73	B
	265/60R18	110	T	8J	1060	250	775	272	9.7	D	D	73	B
	285/60R18	116	T	8 1/2J	1250	250	799	292	9.7	D	D	75	B
	19	225/55R19	99	T	7J	775	250	731	233	9.7	D	D	72
235/50R19		99	T	7 1/2J	775	250	719	245	9.7	D	D	72	B
235/55R19 XL		105	H	7 1/2J	925	290	741	245	9.7	C	D	72	B
245/40R19 XL		98	S	8 1/2J	750	290	679	248	9.2	D	D	72	B
245/45R19		98	T	8J	750	250	703	243	9.7	D	D	72	B
245/55R19		103	T	7 1/2J	875	250	753	253	9.7	C	D	72	B
255/40R19		96	T	9J	710	250	687	260	9.7	D	D	73	B
255/45R19		100	T	8 1/2J	800	250	713	255	9.7	D	D	73	B
255/50R19		103	T	8J	875	250	739	265	9.7	C	D	73	B
255/55R19		107	T	8J	975	250	763	265	9.7	C	D	73	B
265/50R19		106	T	8 1/2J	950	250	749	277	9.7	C	D	73	B
275/35R19		96	T	9 1/2J	710	250	675	278	9.7	D	D	73	B
275/40R19		101	T	9 1/2J	825	250	703	278	9.7	D	D	73	B
275/55R19		111	T	8 1/2J	1090	250	785	284	9.7	D	D	73	B
20	285/45R19	107	T	9 1/2J	975	250	739	285	9.2	D	D	75	B
	235/55R20 XL	105	S	7 1/2J	925	290	766	245	9	C	D	72	B
	245/40R20	95	T	8 1/2J	690	250	704	248	9.7	D	D	72	B
	245/45R20	99	T	8J	775	250	728	243	9.7	D	D	72	B
	245/50R20	102	T	7 1/2J	850	250	754	253	9.7	D	D	72	B
	255/45R20	101	T	8 1/2J	825	250	738	255	9.7	D	D	73	B
	255/50R20 XL	109	H	8J	1030	290	764	265	9.7	C	D	73	B
	255/55R20 XL	110	T	8J	1060	290	788	265	9.7	C	D	73	B
	265/45R20	104	T	9J	900	250	746	266	9.7	D	D	73	B
	265/50R20	107	T	8 1/2J	975	250	774	277	9.7	C	D	73	B
	275/40R20	102	T	9 1/2J	850	250	728	278	9.7	D	D	73	B
	275/45R20 XL	110	T	9J	1060	290	756	273	9.7	C	D	73	B
	275/50R20 XL	113	S	8 1/2J	1150	290	784	284	9	C	D	73	B
	275/55R20	113	T	8 1/2J	1150	250	810	284	9.7	C	D	73	B
21	285/35R20	100	T	10J	800	250	708	290	9.7	D	D	75	B
	285/45R20	108	T	9 1/2J	1000	250	764	285	9.7	D	D	75	B
	285/50R20	112	T	9J	1120	250	794	297	9.7	D	D	75	B
	315/35R20	106	T	11J	950	250	728	320	9.7	D	E	75	B
	255/45R21	102	S	8 1/2J	850	250	763	255	9	D	D	73	B
	265/45R21	104	T	9J	900	250	771	266	9.7	D	D	73	B
	275/45R21	107	T	9J	975	250	781	273	9.7	D	D	73	B
22	275/50R21 XL	113	T	8 1/2J	1150	290	809	284	9.7	D	D	73	B
	285/45R21	109	T	9 1/2J	1030	250	789	285	9.7	D	D	75	B
	295/40R21	107	T	10 1/2J	975	250	769	301	9.7	D	D	75	B
265/40R22 XL	106	S	9 1/2J	950	290	771	271	9	C	D	73	B	

GREEN-Max Winter GRIP²

The Second studdable snow tire with outstanding braking performance on ice&snow condition

Designed for ice and snow surface;

Directional tread pattern design for excellent snow traction performance;

Great grip and handling performance on ice and snow surface.



GREEN-Max Winter Grip

Studdable snow tire with outstanding braking performance on ice&snow condition.

Designed for ice and snow surface;

Directional tread pattern design for excellent snow traction performance;

Great grip and handling performance on ice and snow surface.



RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
14	165/65R14	79	T	5J	437	250	570	170	8.9
	165/70R14	81	T	5J	462	250	588	170	8.9
	175/65R14 XL	86	T	5J	530	290	584	177	8.9
15	175/65R15	84	T	5J	500	250	609	177	8.9
	185/60R15	84	T	5 1/2J	500	250	603	189	8.9
	185/65R15	88	T	5 1/2J	560	250	621	189	8.9
	195/55R15 XL	89	T	6J	580	290	595	201	8.9
	195/65R15 XL	95	T	6J	690	290	635	201	8.9
16	195/45R16 XL	84	T	6 1/2J	500	290	582	195	8.9
	205/45R16 XL	87	T	7J	545	290	590	206	8.9
	205/55R16 XL	94	T	6 1/2J	670	290	632	214	8.9
	205/60R16 XL	96	T	6J	710	290	652	209	8.9
	215/60R16	95	T	6 1/2J	690	250	664	221	8.9
	215/70R16	100	T	6 1/2J	800	250	708	221	8.9
	225/55R16 XL	99	T	7J	775	290	654	233	8.9
17	205/45R17 XL	88	T	7J	560	290	616	206	8.9
	215/55R17 XL	98	T	7J	750	290	642	226	8.9
	225/50R17 XL	98	T	7J	750	290	658	233	8.9
	225/40R18 XL	92	T	8J	630	290	637	230	8.9
18	225/45R18 XL	95	T	7 1/2J	690	290	659	225	8.9
	245/40R18 XL	97	T	8 1/2J	730	290	653	248	8.9
19	225/35R19 XL	88	T	8J	560	290	641	230	8.9
	245/40R19 XL	98	T	8 1/2J	750	290	679	248	8.9

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE Level	
13	155/70R13	75	T	4.50B	387	250	548	157	9.7	E	E	71	B
	155/80R13	79	T	4.50B	437	240	578	157	9.7	E	E	71	B
	165/70R13	79	Q	5.00B	437	250	562	170	9.7	E	E	71	B
	175/70R13	82	T	5.00B	475	250	576	177	9.7	E	E	71	B
14	175/65R14 XL	86	T	5J	530	290	584	177	9.7	E	E	71	B
	185/60R14	82	T	5 1/2J	475	250	578	189	9.7	E	E	71	B
	185/65R14 XL	90	T	5 1/2J	600	290	596	189	9.7	D	E	71	B
	185/70R14 XL	92	T	5 1/2J	630	290	616	189	9.7	D	E	71	B
	185/55R15 XL	86	T	6J	530	290	585	194	9.7	E	E	71	B
15	185/65R15	88	T	5 1/2J	560	250	621	189	9.7	D	E	71	B
	195/60R15 XL	92	T	6J	630	290	615	201	9.7	D	E	72	B
	195/65R15 XL	95	T	6J	690	290	635	201	9.7	D	E	72	B
	205/65R15 XL	99	T	6J	775	290	647	209	9.7	D	E	72	B
	205/55R16 XL	94	T	6 1/2J	670	290	632	214	9.7	D	E	72	B
16	205/60R16 XL	96	T	6J	710	290	652	209	9.7	D	E	72	B
	215/55R16 XL	97	T	7J	730	290	642	226	9.7	D	E	72	B
	215/65R16	98	T	6 1/2J	750	250	686	221	9.7	D	E	72	B
17	215/50R17 XL	95	T	7J	690	290	648	226	9.7	D	E	72	B
	225/45R17 XL	94	T	7 1/2J	670	290	634	225	9.7	D	E	72	B
	225/55R17	97	T	7J	730	250	680	233	9.7	D	E	72	B

GREEN-Max Winter GRIP VAN²

Studdable snow tire with outstanding braking performance on ice&snow condition

Designed for ice and snow surface;

Great grip and handling performance on ice and snow surface.



RIM	Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
10	195/55R10C	/	98/96	N	6.00B	D 710 S 750	625	468	201	10.2
13	155R13C	8PR	90/88	R	4.50B	D 560S 600	450	578	157	10.2
	155R13C	/	91/89	N	4.50B	D 580S 615	450	578	157	10.2
	165R13C	/	96/94	N	4.50B	D 670S 710	450	594	165	10.2
	175R13C	8PR	97/95	Q	5.00B	D 690 S 730	450	610	177	10.2
	195/50R13C	/	104/101	N	6.00B	D 825S 900	650	526	201	10.2
14	185R14C	8PR	102/100	R	5 1/2J	D 800 S 850	450	652	189	10.2
	185R14C	/	102/100	N	5 1/2J	D 800 S 850	450	652	189	10.2
15	195/70R15C	8PR	104/102	R	6J	D 850 S 900	450	655	201	10.2
	215/70R15C	8PR	109/107	R	6 1/2J	D 975 S 1030	450	683	221	10.2
	225/70R15C	8PR	112/110	R	6 1/2J	D 1060 S 1120	450	697	228	10.2
16	185/75R16C	8PR	104/102	R	5J	D 850 S 900	475	684	184	10.2
	195/75R16C	8PR	107/105	R	5 1/2J	D 925 S 975	475	698	196	10.2
	205/65R16C	8PR	107/105	R	6J	D 925 S 975	475	672	209	10.2
	215/65R16C	8PR	109/107	R	6 1/2J	D 975S 1030	475	686	221	10.2
	205/75R16C	8PR	110/108	R	5 1/2J	D 1000 S 1060	475	714	203	10.2
	215/75R16C	10PR	116/114	R	6J	D 1180 S 1250	525	728	216	10.2
	225/65R16C	8PR	112/110	R	6 1/2J	D 1060 S 1120	475	698	228	10.2
	225/75R16C	10PR	121/120	R	6J	D 1400 S 1450	575	744	223	10.2
	235/65R16C	10PR	121/119	R	7J	D 1360S 1450	575	712	240	10.2
17	215/60R17C	8PR	109/107	R	6 1/2J	D 975S 1030	475	690	221	10.2
	235/60R17C	10PR	117/115	Q	7J	D 1215S 1285	525	714	240	10.2



GREEN-Max Winter Grip SUV

Studdable snow tire with outstanding braking performance on ice&snow condition.

Designed for ice and snow surface;

Excellent snow traction performance with directional tread pattern design;

Great grip and handling performance on ice and snow surface;

Designed for SUVs.

RIM	Size	Load Index	Speed Symbols	Standard Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)	EU-Labeling Details			
										RR Level	WG Level	PASS BY NOISE	
										dB	Level		
17	225/65R17 XL	106	T	6 1/2J	950	290	724	228	9.7	D	D	72	B
	235/60R17 XL	106	T	7J	950	290	714	240	9.7	D	D	72	B
	235/65R17 XL	108	T	7J	1000	290	738	240	9.7	D	D	72	B
18	225/55R18	98	T	7J	750	250	705	233	9.7	D	D	72	B
	255/55R18 XL	109	T	8J	1030	290	737	265	9.7	D	D	73	B
	275/60R18 XL	117	T	8J	1285	290	787	279	9.7	C	D	73	B
20	275/45R20 XL	110	T	9J	1060	290	756	273	9.7	C	D	73	B
	275/55R20 XL	117	T	8 1/2J	1285	290	810	284	9.7	C	D	73	B